

PV-ezRack PostMount-A

Robust pole mount system with adjustable angle from one to four panels



PV-ezRack PostMount-A

Clenergy's PV-ezRack PostMount-A delivers flexible and durable designs to mount from one to four panels per post. It's ideal for remote off-grid applications such as water pumps or small residential and commercial systems. The panel tilt is easily adjustable between 0° and 60° throughout the year and comes with hassle-free mounting thanks to patented components such as the PV-ezRack rails and clamps. The combination of high quality aluminium, stainless steel and galvanised steel components make this a robust, reliable system with excellent corrosion resistance.

PM1-A

Main Benefits

Suitable for every soil condition

With its concrete foundation. PostMount-A can be installed on even or uneven ground or on a slope, making it suitable for any soil type and a wide range of applications.

Adjustable tilt angle

The steel cap (post head) is designed to tilt panels between 10° and 60° to ensure that you get the required power output you need anywhere, anytime. Changing the angle merely requires a single pair of spanners.

Robust and reliable

Mounted on aluminium rails the panels are supported by robust galvanised steel landscape and master tubes secured with stainless steel bolts. The post is fixed in to a concrete foundation.

Quick and easy installation

Innovative and internationally patented, the Z-Module technology is used in almost all PV-ezRack components. The Z-Module provides a quick, easy and safe installation method and can be inserted in to the rail at any given point, secured with just three hand grips.



International Patent PCT/AU2009/000616



Inter and End clamps

Using the patented Clenergy Z-module, PV-ezRack Inter and End clamps offer a simple, easy to use and robust fixing of PV panels of any size. Compatible clamps for thin film modules are also available

ER-P

Post

This is a steel post with the outside diameter of 102mm (wall thickness 6mm), which is embedded in to concrete. It is also available with welded mounting plate (flange).

ER-SC

Steel cap

angles.



Master tube

The master tube connects to the adjustable tube and steel cap. It is a robust galvanised steel profile and holds theangle brackets or the landscape tubes with U-bolts.





ER-R-ECO

ECO-Rail

Specifically developed to achieve larger spans, the design of the aluminium ECO-Rail enables faster installation. The ECO-Rails have two patented Z-Module channels with one at top for panel mounting and the second on side which connects to the PostMount-A structure.









Worldwide network





Clenergy PV-ezRack PostMount 2-A, 3-A and 4-A brochure V201712



Clenergy America 400 Continental Blvd, 6th Floor, El Segundo, CA 90245 Tel: +1 310-426-2617

Clenergy Australia

1/10 Duerdin Street, Clayton VIC 3168 Australia Tel: +61 3 9239 8088 Fax: +61 3 9239 8024 E-mail: sales@clenergy.com.au www.clenergy.com.au

Clenergy China 999-1009 Min'an Rd, Huoju Hi-tech Ind. Dev. Zone Xiang'an District 361101, Xiamen, Fujian, China Tel: +86 592 311 0088 Fax: +86 592 599 5028 E-mail: sales@clenergy.com.cn www.clenergy.com.cn

Clenergy Europe

Clenergy Court, Blisworth Hill Farm Stoke Road, Blisworth Northampton, NN7 3DB, UK Tel: +44 1604 857 674 Fax: +44 1604 858 620 E-mail: sales_uk@clenergy.com www.clenergy.uk.com

Clenergy Japan SOHO STATION 401, 24-8 Yamashita-cho, Naka-ku Yokohama, 231-0023 Japan Tel: +81 45 228 8226 Fax: +81 45 228 8316 E-mail: sales@clenergy.co.jp www.clenergy.jp

Clenergy Philippines

145 Yakal St., San Antonio village, Makati City, Philippines Tel: +63 977 8407282 +63 977 8407240 E-mail: sales_ph@clenergy.com www.clenergy.ph

Clenergy Malaysia (Regional Office)

Suite 8,01, Level 8, Menara IGB, Mid Valley City Lingkaran Syed Putra, 59200,Kuala Lumpur, Malaysia Phone: +60 3 2202 4268 Fax: +60 3 2202 4001 E-mail: sales@clenergy.my www.clenergy.my

Clenergy Thailand

9/2, 5th Floor, Vorasin Building, Soi Yasoob 2, Viphavadee-Rungsit Road, Chomphon Sub-district, Chatuchak District, Bangkok 10900 Tel: +66 63 228 0200, +66 81 969 5152 E-mail: sales_th@clenergy.com,support_th@clenergy.com