

BIANCO **iCON**
SERIES**CONTROLS**

**iCON Series
Controls**



BIANCO **iCON**
SERIES

BIANCO **CON**
SERIES**PUMPS**

BIANCO **CON**
SERIES**DRIVES**

BIANCO **iCON**
SERIES**CONTROLS**

BIANCO **iCON**
SERIES**FILTRATION**

Introducing the Bianco iCON range of intelligent controllers.

The iCON range of intelligent controllers are suitable for installation in various Industrial and Domestic applications.

Controllers are generally used in pumping applications where control of single or multiple pumps are required. Settings for drainage, pressure boosting and transfer applications are easily accomplished by function switches. The iCON intelligent controller is user friendly with many features for controlling your pumps, protecting your pumps and also reporting of faults with live data and historical data retention. Control of your pumps is also possible from a slave controller which is included with each iCON intelligent controller as standard.

The iCON controller is supplied standard with RS485 communication interface for easy integration into your Building Management System.

The iCON controller enclosure has an ingress protection rating IP54 with an intelligent dynamic LCD display for pump running information and is suitable for installation both indoors and outdoors. Automatic calibration of the iCON intelligent controller is easily completed to set your pump thermal overload by means of push buttons.

Optional lockable enclosure available as an accessory to prevent access to pump controller or allow fitting of motor capacitor(s).



iCON Series Controls | SPECIFICATIONS

iCON BIA-SPC Single Pump Controller

Available in single phase up to 2.2kW and three phase up to 15kW.

FEATURES

- IP54 engineered plastic enclosure
- Intelligent real time LCD displays pump running information
- Intelligent push button pump overload calibration prompts for uncompleted calibration
- Function switch setting for drainage, pressure boosting or transfer applications
- Level controls can be float switches or probes
- Auto, manual switching
- Visual and audible alarms
- Adjustable time delay for audible alarm
- Low voltage control circuit
- RS485 communication interface (BMS, MODBUS)
- Pump accumulated run time display
- Last five pump faults logged into memory
- Slave controller included
- Control box contains MCB and DOL contactor
- Provision for combinations of multiple device inputs and outputs for use with float switches, probes, pressure switches or external device alarms.

PROTECTION

- Pump stalled
- Overload (restart attempt every 30 min. adj.)
- Short circuit
- Over voltage (restart attempt every 5 min. adj.)



- Under voltage (restart attempt every 5 min. adj.)
- Repeated starts (more than 5 per minute)
- Open phase (3 phase only)
- Phase reversal (3 phase only)
- Three phase imbalance (3 phase only)
- Over temperature (where pumps are fitted with micro-therms)
- Anti-seize run timer (3sec every 240 hrs, adjustable)
- Dry run protection without need for a float switch or liquid level probe (restart attempt every 30 min. adj.)

Models available:

BIA-SPC1-22 (240V, 2.2kW)
BIA-SPC3-40 (415V, 4kW)
BIA-SPC3-110 (415V, 11kW)
BIA-SPC3-150 (415V, 15kW)

iCON BIA-DPC Dual Pump Controller

Available in single phase up to 2.2kW and three phase up to 15kW.

FEATURES

- IP54 engineered plastic enclosure
- Intelligent real time LCD displays pump running information
- Intelligent push button pump overload calibration prompts for uncompleted calibration
- Function switch setting for drainage, pressure boosting or transfer applications
- Level controls can be float switches or probes
- Auto, manual switching
- Visual and audible alarms
- Adjustable time delay for audible alarm
- Low voltage control circuit
- RS485 communication interface (BMS, MODBUS)
- Pump accumulated run time display
- Last five pump faults logged into memory
- Slave controller included
- Control box contains MCB and DOL contactor
- Provision for combinations of multiple device inputs and outputs for use with float switches, probes, pressure switches or external device alarms
- Alternate pump starts, Automatic duty pump cycling and load sharing.

PROTECTION

- Pump stalled
- Overload (restart attempt every 30 min. adj.)



- Short circuit
- Over voltage (restart attempt every 5 min. adj.)
- Under voltage (restart attempt every 5 min. adj.)
- Repeated starts (more than 5 per minute)
- Open phase (3 phase only)
- Phase reversal (3 phase only)
- Three phase imbalance (3 phase only)
- Over temperature (where pumps are fitted with micro-therms)
- Anti-seize run timer (3sec every 240 hrs, adjustable)
- Dry run protection without need for a float switch or liquid level probe (restart attempt every 30 min. adj.)

Models available:

BIA-DPC1-22 (240V, 2.2kW)
BIA-DPC3-40 (415V, 4kW)
BIA-DPC3-110 (415V, 11kW)
BIA-DPC3-150 (415V, 15kW)

iCON BIA-iALARM Liquid Level Alarm


FEATURES

- 240V, single phase power supply. 10A rated.
- Safe 12V low voltage for float switch
- MODE button to switch easily between high level and low level warning.
- PULSE button to switch easily between continuous and intermittent audible warning. In intermittent mode, the audible alarm will sound initially, then every 5 minutes.
- MUTE button to silence the alarm. Visual alarm remains on until alarm situation is rectified.
- 10m float switch complete with counter weight supplied and wired.
- Liquid level alarm can be mounted up to 50m from the tank using low voltage cabling (optional extra)
- IP54



Applications

Stormwater	Rainwater
Sewage	Effluent
Grey Water	



Slave Controller

FEATURES

- Slave Controller (SC) unit included with each pump controller. Uses USB cable or RS485 (STP) cable to communicate up to 1200m from pump controller. All pump control functions of master unit available through the slave controller except pump calibration and parameter setting.



WHITE INTERNATIONAL PTY LTD

52-60 Ashford Ave Milperra NSW 2214
PO Box 304 Milperra LPO NSW 2214
Phone 02 9783 6000 Fax 02 9783 6001
Customer Service Hotline 1300 783 601
Email Sales: pumpsales@whiteint.com.au
General info: info@whiteint.com.au

www.whiteint.com.au

WHITE INTERNATIONAL NZ LTD

15G Kerwyn Avenue, East Tamaki
Auckland 2013, New Zealand
Phone 09 579 9777 Fax 09 579 7775
Customer Service Hotline 0800 509 506
Customer Service Faxline 0800 804 344
Email Sales: sales@whiteint.co.nz
General info: info@whiteint.co.nz

www.whiteint.co.nz

