



PUMP PRODUCTS



Domestic

**Drainage /
Sewage**



**Packaged
Pump Stations**

Industrial



**Engine
Powered
Lubrication**

**Rain
Harvesting**



**Pool
Equipment**

**Pressure
Tanks**


Aquatics





TERMS AND CONDITIONS


Our warranty commences from the date of purchase and is not transferable. The warranty only covers the original owner, purchaser or end user and is subject to the Trade Practices Act and Goods and Consumer Protection legislation of the various states. Proof of purchase along with appropriate documentations is required before consideration under warranty is given.

PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------

SUBMERSIBLE DRAINAGE & VORTEX PUMPS			
<p>Reinforced Inert Plastic Body Non-Corrosive For Long Life Built In Rigid Float Activated Automatic Switch Factory Set For Reliable Operation, Eliminate Float Cable Failure Stainless Steel Shaft And Screws Corrosion Resistant For Longer Life Repairable Longer Service Life Ball Bearings Longer Life And Quiet Operation Ground Rotor Shaft, Triple Lip Seals In Oil Chamber Longer Seal And Pump Life 2 Year DAB Pump Warranty</p>			
SUBMERSIBLE DRAINAGE PUMPS			
DAB-NOVA180A	0.22 kW, 0.3 hp, 240V, AUTOMATIC	295.00	
DAB-NOVA200	0.22 kW, 0.3 hp, 240V, MANUAL	300.00	
DAB-NOVA300A	0.22 kW, 0.3 hp, 240V, AUTOMATIC	330.00	
DAB-NOVA600A	0.55 kW, 0.75 hp, 240V, AUTOMATIC	497.00	
SUBMERSIBLE 'VORTEX' PUMP			
DAB-FEKA600A	0.55 kW, 0.75 hp, 240V, AUTOMATIC	510.00	


SUBMERSIBLE MULTI-PURPOSE 'VORTEX' DRAINAGE PUMP			
<p>Ideal for drainage, emptying, pumping water between containers and small irrigation. Suitable to pump dirty water containing particles with maximum diameter up to 30mm. Anti corrosive and rust proof materials. Motor with thermic overload protection. Wear resistant shaft and impeller. Excellent cooling in the motor shaft that enables the pump to operate even when it is partially submerged. Automatic version with start / stop float switch. Supplied with power cable with plug and self sealing fitting. 2 Year DAB Pump Warranty</p>			
DAB-FEKA300A	0.22 kW, 0.3 hp, 240V, AUTOMATIC	270.00	

SUBMERSIBLE STAINLESS STEEL DRAINAGE PUMPS			
<p>Pump completely in stainless steel AISI 304 with thrust ring type impeller for draining clear waste water containing solids of max 10 mm diameter. Through body cooling. AISI 316 stainless steel motor shaft. Double mechanical seal with interposed oil chamber (non-toxic oil) Cable Length: 10 metres. Easy and rapid maintenance 2 Year DAB Pump Warranty</p>			
DAB-DRENAG1000MA	1.0 kW, 1.36 hp, 240V Flows to 392 l/min, heads to 15.3 m	1599.00	
DAB-DRENAG1200MA	1.2 kW, 1.6 hp, 240V Flows to 465 l/min, heads to 17m	1759.00	


SUBMERSIBLE STAINLESS STEEL VORTEX PUMPS			
<p>Pump completely in stainless steel AISI 304 and microcasting stainless steel impeller. Double mechanical seal with interposed oil chamber (non-toxic oil). VS - Full Stainless Steel. Cable Length: 10 metres. 2 Year DAB Pump Warranty</p>			
DAB-FEKAVS550MA	0.55 kW, 0.75 hp, flows to 330 l/m, heads to 7.4 m	945.00	
DAB-FEKAVS750MA	0.75 kW, 1.0 hp, flows to 400 l/m, heads to 9.6 m	1109.00	
DAB-FEKAVS1000MA	1.0 kW, 1.36 hp, flows to 450 l/m, heads to 11.8 m	1359.00	
DAB-FEKAVS1200MA	1.2 kW, 1.6 hp, flows to 533 l/m, heads to 14.0 m	1535.00	


PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------


PACKAGED PUMP STATIONS
UNDER BASIN PUMP STATION - GREY WATER PUMP UNIT

DAB-NOVABOX30-300M	30 LITRE NOVA300 PUMP FITTED 30 litre under basin automatic collecting station. Features 30 litre technopolymer container Fitted with 240 volt automatic DAB-NOVA300A drainage pump 5 metre power lead Discharge check valve Flow rates from 16l/m to 120l/m, Heads up to 6 meters Suitable for water temperature up to 50 degrees C in normal operation and up to 90 degrees C for 3 minutes 2 YEAR DAB Pump Warranty * Parts and Labour	1007.00	
---------------------------	--	----------------	---

BLUEBOX POLYETHYLENE LIFTING STATIONS


ZEN-BLUEBOXDG	250 litre Collecting Station for Waste Water. Features 250 litre polyethylene tank 600mm high x 900mm long x 500mm wide Constructed for either in ground or above ground installation Able to handle liquids such as raw sewage, trade waste, effluent and storm water 1 1/2" galvanised outlet pipework and gaskets Installation accessories 12 MONTHS ZENIT BLUEBOX Warranty *Parts and Labour	1661.00	 Blue Box Standard
----------------------	---	----------------	--


ZEN-BLUEBOXDGBLUE40M	ZEN-BLUEBOXDG with ZEN-DGBLUE40/2/G40VMG fitted	2701.00	 Blue Box featuring Zenit DG Blue Vortex Pump
ZEN-BLUEBOXDGBLUE50M	ZEN-BLUEBOXDG with ZEN-DGBLUE50/2/G40VMG fitted	2742.00	
ZEN-BLUEBOXDGBLUE75M	ZEN-BLUEBOXDG with ZEN-DGBLUE75/2/G40VMG fitted	2857.00	
ZEN-BLUEBOXDGBLUE100M	ZEN-BLUEBOXDG with ZEN-DGBLUE100/2/G40VMG fitted 12 MONTHS ZENIT BLUEBOX Warranty * Parts and labour 2 YEAR ZENIT BLUE SERIES Pump Warranty * Parts and Labour	3013.00	


ZEN-BLUEBOXGR	250 litre Automatic Collecting Station for Domestic and Industrial Sewage. Features Coupling foot with 2" vertical outlet and built in air bleed 2" ball type non return valve 2" galvanised outlet pipework and gaskets Installation accessories	2581.00	 Blue Box featuring guide rails ball type non return valve & Zenit GR Blue Grinder Pump
ZEN-BLUEBOXGRBLUEP100M	ZEN-BLUEBOXGR with ZEN-GRBLUEP100/2/G40HMG fitted	4435.00	
ZEN-BLUEBOXGRBLUEP150M	ZEN-BLUEBOXGR with ZEN-GRBLUEP150/2/G40HMG fitted	4739.00	
ZEN-BLUEBOXGRBLUEP200M	ZEN-BLUEBOXGR with ZEN-GRBLUEP200/2/G40HMG fitted 12 MONTHS ZENIT BLUEBOX Warranty * Parts and Labour 2 YEAR ZENIT BLUE SERIES Pump Warranty * Parts and Labour	5607.00	


PUMPS


PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------

DR BLUE SERIES -Open multi-vane fully submerged impeller			
DR Blue series of submersible drainage pumps for domestic and professional use. DR (DRENO) version with multi-vane fully submerged plastic impeller for efficient operation. Float switch standard on single-phase versions. 10 m power lead (with 3 pin plug on single-phase pumps). Suits outdoor installations. Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. Longer seal life. Anti-stressing system for power cable. Reduces cable damage and water entry. Cable holder grommet built into handle. Allows adjustment of float switch cable length. Cast iron pump body. For durability. Suction screen. To keep out hard solids. Ergonomic plastic carry handle. For safety and comfort. 2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour			
ZEN-DRBLUE40/2/G32VMG	0.30 kW, 0.40 hp 240V with float switch, max 7 m h, 210 l/m	610.00	
ZEN-DRBLUE50/2/G32VMG	0.37 kW, 0.50 hp 240V with float switch, max 9.5 m h, 240 l/m	680.00	
ZEN-DRBLUE75/2/G32VMG	0.55 kW, 0.75 hp 240V with float switch, max 12 m h, 300 l/m	772.00	
ZEN-DRBLUE100/2/G32VMG	0.75 kW, 1.00 hp 240V with float switch, max 14 m h, 330 l/m	948.00	

DG BLUE SERIES - Vortex recessed impeller			
DG Blue series series of submersible vortex pumps for domestic and professional use. DG (DRAGA) version with vortex recessed plastic impeller to pass soft solids to 35mm diameter. Float switch standard on single-phase versions. 10 m power lead (with 3 pin plug on single-phase pumps). Suits outdoor installations. Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. Longer seal life. Anti-stressing system for power cable. Reduces cable damage and water entry. Cable holder grommet built into handle. Allows adjustment of float switch cable length. Cast iron pump body. For durability. Cast iron support base. Assists in the passage of soft solids to 35mm. Ergonomic plastic carry handle. For safety and comfort. 2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour			
ZEN-DGBLUE40/2/G40VMG	0.30 kW, 0.40 hp 240V with float switch, max 6 m h, 270 l/m	729.00	
ZEN-DGBLUE50/2/G40VMG	0.37 kW, 0.50 hp 240V with float switch, max 7.8 m h, 290 l/m	776.00	
ZEN-DGBLUE75/2/G40VMG	0.55 kW, 0.75 hp 240V with float switch, max 10 m h, 420 l/m	892.00	
ZEN-DGBLUE100/2/G40VMG	0.75 kW, 1.00 hp 240V with float switch, max 11.5 m h, 430 l/m	1048.00	

DR BLUE PROFESSIONAL SERIES - Open multi-vane fully submerged impeller			
New series of submersible drainage pumps for industrial / commercial and professional use. DR (DRENO) version with multi-vane fully submerged cast iron impeller for efficient operation. Float switch standard on single-phase versions. 10 m power lead (with 3 pin plug on single-phase pumps). Suits outdoor installations. Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. Longer seal life. Anti-stressing system for power cable. Reduces cable damage and water entry. Cable holder grommet built into handle. Allows adjustment of float switch cable length. Cast iron pump body. For durability. Suction screen. To keep out hard solids. Aluminium handle suction strainer stainless steel Built in Air Bleed 2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour			
ZEN-DRBLUEP150/2/G50VMG	1.1 kW, 1.5 hp 240V with float switch, max 14.6 m h, 600 l/m	1364.00	
ZEN-DRBLUEP150/2/G50VM	1.1 kW, 1.5 hp 240V without float switch, max 14.6 m h, 600 l/m	1338.00	
ZEN-DRBLUEP200/2/G50VMG	1.5 kW, 2.0 hp 240V with float switch, max 18 m h, 630 l/m	1616.00	
ZEN-DRBLUEP200/2/G50VM	1.5 kW, 2.0 hp 240V without float switch, max 18 m h, 630 l/m	1590.00	
ZEN-DRBLUEP150/2/G50VT	1.1 kW, 1.5 hp 415V without float switch, max 14.6 m h, 600 l/m	1310.00	
ZEN-DRBLUEP200/2/G50VT	1.5 kW, 2.00 hp 415V without float switch, max 18 m h, 630 l/m	1590.00	

PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------

DG BLUE PROFESSIONAL SERIES - VORTEX PUMPS

New series of submersible vortex pumps for industrial / commercial and professional use. DG (DRAGA) version with vortex recessed cast iron impeller to pass soft solids to 35mm diameter. Float switch standard on single-phase versions. 10 m power lead (with 3 pin plug on single-phase pumps). **Suits outdoor installations.** Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. **Longer seal life.** Anti-stressing system for power cable. **Reduces cable damage and water entry.** Cable holder grommet built into handle. **Allows adjustment of float switch cable length.** Cast iron pump body. **For durability.** Cast Iron support base. **Assists in the passage of soft solids to 35mm.** Aluminium handle suction strainer stainless steel. Built in Air Bleed

2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour

ZEN-DGBLUEP150/2/G50VMG	1.1 kW, 1.5 hp 240V with float switch, max 12.5 m h, 600 l/m	1325.00
ZEN-DGBLUEP150/2/G50VM	1.1 kW, 1.5 hp 240V without float switch, max 12.5 m h, 600 l/m	1299.00
ZEN-DGBLUEP200/2/G50VMG	1.5 kW, 2.0 hp 240V with float switch, max 15 m h, 690 l/m	1553.00
ZEN-DGBLUEP200/2/G50VM	1.5 kW, 2.0 hp 240V without float switch, max 15 m h, 690 l/m	1527.00
ZEN-DGBLUEP150/2/G50VT	1.1 kW, 1.5 hp 415V without float switch, max 12.5 m h, 600 l/m	1325.00
ZEN-DGBLUEP200/2/G50VT	1.5 kW, 2.0 hp 415V without float switch, max 15 m h, 690 l/m	1553.00



GR BLUE PROFESSIONAL SERIES - GRINDER PUMPS

Submersible electric pumps with **high head cast iron impeller and cutter**, with 69,000 cuts per minute. The GR Models are equipped with an intake cutting system composed of a steel plate and a triangular rotary cutter. The system fibres and stringy bodies and assures smooth pump functioning. 10 m power lead (with 3 pin plug on single-phase pumps). **Suits outdoor installations.** Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. **Longer seal life.** Anti-stressing system for power cable. **Reduces cable damage and water entry.** Cable holder grommet built into handle. **Allows adjustment of float switch cable length.** Cast iron pump body. **For durability.** Cast Iron support base. **Assists in the passage of soft solids to 35mm.** Ergonomic metallic carry handle. **For safety and comfort.**

2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour

ZEN-GRBLUEP100/2/G40HMG	0.75 kW, 1.0 hp 240V with float switch, max 17.4 m h, 240 l/m	1854.00
ZEN-GRBLUEP100/2/G40HM	0.75 kW, 1.0 hp 240V without float switch, max 17.4 m h, 240 l/m	1828.00
ZEN-GRBLUEP150/2/G40HMG	1.1 kW, 1.5 hp 240V with float switch, max 20.0 m h, 300 l/m	2158.00
ZEN-GRBLUEP150/2/G40HM	1.1 kW, 1.5 hp 240V without float switch, max 20.0 m h, 300 l/m	2132.00
ZEN-GRBLUEP200/2/G40HMG	1.5 kW, 2.0 hp 240V with float switch, max 26.2 m h, 300 l/m	3026.00
ZEN-GRBLUEP200/2/G40HM	1.5 kW, 2.0 hp 240V without float switch, max 26.2 m h, 300 l/m	3000.00
ZEN-GRBLUEP100/2/G40HT	0.75 kW, 1.0 hp 415V without float switch, max 17.4 m h, 240 l/m	1754.00
ZEN-GRBLUEP150/2/G40HT	1.1 kW, 1.5 hp 415V without float switch, max 20.0 m h, 300 l/m	2046.00
ZEN-GRBLUEP200/2/G40HT	1.5 kW, 2.0 hp 415V without float switch, max 26.2 m h, 300 l/m	2948.00



AP BLUE PROFESSIONAL SERIES - HIGH HEAD

Submersible electric pumps with **high head cast iron impeller.** The AP models can be used in treatment of slightly soiled waters with small solid bodies. The intake strainer allows free passage up to 7mm. 10 m power lead (with 3 pin plug on single-phase pumps). Flanged and threaded delivery outlet for maximum installation versatility. **Suits outdoor installations.** Patented sealing system incorporating dual silicon carbide / graphite alumina mechanical seals in oil bath. **Longer seal life.** Anti-stressing system for power cable. **Reduces cable damage and water entry.** Cable holder grommet built into handle. **Allows adjustment of float switch cable length.** Cast iron pump body. **For durability.** Cast Iron support base. Ergonomic metallic carry handle. **For safety and comfort.**


2 YEAR ZENIT BLUE SERIES PUMP WARRANTY * Parts and labour

ZEN-APBLUEP100/2/G40HMG	0.75 kW, 1.0 hp 240V with float switch, max 17.2 m h, 300 l/m	1408.00
ZEN-APBLUEP100/2/G40HM	0.75 kW, 1.0 hp 240V without float switch, max 17.2 m h, 300 l/m	1382.00
ZEN-APBLUEP150/2/G40HMG	1.1 kW, 1.5 hp 240V with float switch, max 19.8 m h, 300 l/m	1638.00
ZEN-APBLUEP150/2/G40HM	1.1 kW, 1.5 hp 240V without float switch, max 19.8 m h, 300 l/m	1612.00
ZEN-APBLUEP200/2/G40HMG	1.5 kW, 2.0 hp 240V with float switch, max 25.7 m h, 360 l/m	1922.00
ZEN-APBLUEP200/2/G40HM	1.5 kW, 2.0 hp 240V without float switch, max 25.7 m h, 360 l/m	1896.00
ZEN-APBLUEP100/2/G40HT	0.75 kW, 1.0 hp 415V without float switch, max 17.2 m h, 300 l/m	1318.00
ZEN-APBLUEP150/2/G40HT	1.1 kW, 1.5 hp 415V without float switch, max 19.8 m h, 300 l/m	1537.00
ZEN-APBLUEP200/2/G40HT	1.5 kW, 2.0 hp 415V without float switch, max 25.7 m h, 360 l/m	1824.00



PUMPS



PART NO.	Description	LIST PRICE	Illustration
DRE DRAINAGE VERTICAL OUTLET			 <p style="text-align: center;">Shown with float</p>
Heavy duty cast iron submersible drainage pumps suitable for domestic and industrial applications. These pumps can be installed in underground car parks to pump water and oily substances. These pumps are ideal for pumping clean water or dirty water without solids, are easy to install and are equipped with our without float switches. Ecological dry motor Open multi channel cast iron impeller. Free passage 10x20mm 240V or 415V pumps with vertical or horizontal outlets 10m H07RN-F power cable			
12 Months ZENIT PUMP Warranty * Parts and Labour <i>Note: Silicon carbide seals becoming standard</i>			
ZEN-DRE50/2/G32VMG	0.37 kW, 0.5 hp 240V with float switch max 8.7 m h, 240 l/m	896.00	
ZEN-DRE75/2/G32VMG	0.55 kW, 0.75 hp 240V with float switch max 12.2 m h, 360 l/m	957.00	
ZEN-DRE100/2/G50VMG	0.88 kW, 1.2 hp 240V with float switch max 12.5 m h, 540 l/m	1234.00	
ZEN-DRE200/2/G50VMG	1.5 kW, 2.0 hp 240V with float switch max 18.1 m h, 720 l/m	1791.00	
ZEN-DRE50/2/G32VM	0.37 kW, 0.5 hp 240V without float switch max 8.7 m h, 240 l/m	869.00	
ZEN-DRE75/2/G32VM	0.55 kW, 0.75 hp 240V without float switch max 12.2 m h, 360 l/m	931.00	
ZEN-DRE100/2/G50VM	0.88 kW, 1.2 hp 240V without float switch max 12.5 m h, 540 l/m	1207.00	
ZEN-DRE200/2/G50VM	1.5 kW, 2.0 hp 240V without float switch max 18.1 m h, 720 l/m	1765.00	
ZEN-DRE100/2/G50VT	0.88 kW, 1.2 hp 415V without float switch max 12.5 m h, 540 l/m	1234.00	
ZEN-DRE200/2/G50VT	1.5 kW, 2.0 hp 415V without float switch max 18.1 m h, 720 l/m	1791.00	

DRE DRAINAGE HORIZONTAL OUTLET		
Heavy duty cast iron submersible drainage pumps suitable for domestic and industrial applications. These pumps can be installed in underground car parks to pump water and oily substances. These pumps are ideal for pumping clean water or dirty water without solids, are easy to install and are equipped with our without float switches. Ecological dry motor Open multi channel cast iron impeller. Free passage 10x20mm 240V or 415V pumps with vertical or horizontal outlets 10m H07RN-F power cable		
12 Months ZENIT PUMP Warranty * Parts and Labour <i>Note: Silicon carbide seals becoming standard</i>		
ZEN-DRE100/2/G50HMG	0.88 kW, 1.2 hp 240V with float switch max 12.5 m h, 540 l/m	1264.00
ZEN-DRE200/2/G50HMG	1.5 kW, 2.0 hp 240V with float switch max 18.1 m h, 720 l/m	1813.00
ZEN-DRE100/2/G50HM	0.88 kW, 1.2 hp 240V without float switch max 12.5 m h, 540 l/m	1238.00
ZEN-DRE200/2/G50HM	1.5 kW, 2.0 hp 240V without float switch max 18.1 m h, 720 l/m	1787.00
ZEN-DRE100/2/G50HT	0.88 kW, 1.2 hp 415V without float switch max 12.5 m h, 540 l/m	1264.00
ZEN-DRE200/2/G50HT	1.5 kW, 2.0 hp 415V without float switch max 18.1 m h, 720 l/m	1813.00

DGE 'VORTEX' VERTICAL OUTLET		
Heavy duty cast iron submersible vortex pumps suitable for domestic and industrial applications. These pumps can be installed in underground car parks to pump water and oily substances. These pumps are ideal for pumping clean water or dirty water with solids up to 35mm such as pits and sewers. Easy to install and are equipped with our without float switches. Recessed vortex type cast iron impeller. Ecological dry motor 240V or 415V pumps with vertical or horizontal outlets 10m H07RN-F power cable		
12 Months ZENIT PUMP Warranty * Parts and Labour <i>Note: Silicon carbide seals becoming standard</i>		
ZEN-DGE50/2/G50VMG	0.37 kW, 0.5 hp 240V with float switch max 6.0 m h, 240 l/m	1032.00
ZEN-DGE75/2/G50VMG	0.55 kW, 0.75 hp 240V with float switch max 8.1 m h, 360 l/m	1093.00
ZEN-DGE100/2/G50VMG	0.88 kW, 1.2 hp 240V with float switch max 12.5 m h, 480 l/m	1387.00
ZEN-DGE200/2/G50VMG	1.5 kW, 2.0 hp 240V with float switch max 15.5 m h, 600 l/m	1892.00
ZEN-DGE50/2/G50VM	0.37 kW, 0.5 hp 240V without float switch max 6.0 m h, 240 l/m	1005.00
ZEN-DGE75/2/G50VM	0.55 kW, 0.75 hp 240V without float switch max 8.1 m h, 360 l/m	1067.00
ZEN-DGE100/2/G50VM	0.88 kW, 1.2 hp 240V without float switch max 12.5 m h, 480 l/m	1361.00
ZEN-DGE200/2/G50VM	1.5 kW, 2.0 hp 240V without float switch max 15.5 m h, 600 l/m	1866.00
ZEN-DGE100/2/G50VT	0.88 kW, 1.2 hp 415V without float switch max 12.5 m h, 480 l/m	1387.00
ZEN-DGE200/2/G50VT	1.5 kW, 2.0 hp 415V without float switch max 15.5 m h, 600 l/m	1872.00

PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------

DGE 'VORTEX' HORIZONTAL OUTLET

Heavy duty cast iron submersible vortex pumps suitable for domestic and industrial applications. These pumps can be installed in underground car parks to pump water and oily substances. These pumps are ideal for pumping clean water or dirty water with solids up to 35mm such as pits and sewers. Easy to install and are equipped with our without float switches. Recessed vortex type cast iron impeller. Ecological dry motor 240V or 415V pumps with vertical or horizontal outlets 10m H07RN-F power cable

12 Months ZENIT PUMP Warranty * Parts and Labour

Note: Silicon carbide seals becoming standard

ZEN-DGE50/2/G50HMG	0.37 kW, 0.5 hp 240V with float switch max 6.0 m h, 240 l/m	1102.00
ZEN-DGE75/2/G50HMG	0.55 kW, 0.75 hp 240V with float switch max 8.1 m h, 360 l/m	1124.00
ZEN-DGE100/2/G50HMG	0.88 kW, 1.2 hp 240V with float switch max 12.5 m h, 480 l/m	1418.00
ZEN-DGE200/2/G50HMG	1.5 kW, 2.0 hp 240V with float switch max 15.5 m h, 600 l/m	1927.00
ZEN-DGE50/2/G50HM	0.37 kW, 0.5 hp 240V without float switch max 6.0 m h, 240 l/m	1076.00
ZEN-DGE75/2/G50HM	0.55 kW, 0.75 hp 240V without float switch max 8.1 m h, 360 l/m	1098.00
ZEN-DGE100/2/G50HM	0.88 kW, 1.2 hp 240V without float switch max 12.5 m h, 480 l/m	1392.00
ZEN-DGE200/2/G50HM	1.5 kW, 2.0 hp 240V without float switch max 15.5 m h, 600 l/m	1901.00
ZEN-DGE100/2/G50HT	0.88 kW, 1.2 hp 415V without float switch max 12.5 m h, 480 l/m	1418.00
ZEN-DGE200/2/G50HT	1.5 kW, 2.0 hp 415V without float switch max 15.5 m h, 600 l/m	1927.00



GRS / GRE - GRINDER

Heavy duty cast iron submersible grinder pumps suitable for both commercial and industrial applications. Open multi-channel impeller with crushing system. Anti clogging system that reduces pump blockages Stainless steel carry handle, bolts and screws Motor casing and pump body made of cast iron Ecological dry motor Mechanical seal made of wear proof Silicon carbide and seal ring Extra strong stainless steel cutting system 10m H07RN-F power cable

12 Months ZENIT PUMP Warranty * Parts and Labour

ZEN-GRS100/2/G40HMGSIC	0.9 kW, 1.2 hp 240V with float switch, max 20.0 m h, 250 l/m	2340.00
ZEN-GRS100/2/G40HMSIC	0.9 kW, 1.2 hp 240V without float switch, max 20.0 m h, 250 l/m	2219.00
ZEN-GRS100/2/G40HTSIC	0.9 kW, 1.2 hp 415V without float switch, max 20.0 m h, 250 l/m	2184.00
ZEN-GRE200/2/G50HMGSIC	1.7 kW, 2.3 hp 240V with float switch, max 24.0 m h, 400 l/m	3521.00
ZEN-GRE200/2/G50HMSIC	1.7 kW, 2.3 hp 240V without float switch, max 24.0 m h, 400 l/m	3494.00
ZEN-GRE200/2/G50HTSIC	1.7 kW, 2.3 hp 415V without float switch, max 24.0 m h, 400 l/m	3405.00



DRN / DRP DRAINAGE

ZEN-DRN300/2/65T	2.2 kW, 3.0 hp 415V without float switch, max 19.4 m h, 1440 l/m Note 1	2481.00
ZEN-DRN400/2/65T	3.0 kW, 4.0 hp 415V without float switch, max 17.2 m h, 1440 l/m Note 2	3306.00
ZEN-DRN550/2/65T	4.1 kW, 5.5 hp 415V without float switch, max 21.6 m h, 1800 l/m Note 2	3529.00
ZEN-DRN300/2/80T	2.2 kW, 3.0 hp 415V without float switch, max 20.0 m h, 1440 l/m Note 1	2623.00
ZEN-DRN400/2/80T	3.0 kW, 4.0 hp 415V without float switch, max 18.6 m h, 1620 l/m Note 2	3363.00
ZEN-DRN550/2/80T	4.1 kW, 5.5 hp 415V without float switch, max 23.2 m h, 1800 l/m Note 2	3588.00
ZEN-23.331	RING STAND	67.00
ZEN-23.180	RING STAND	212.00
ZEN-DRP750/2/80T	7.2 kW, 9.6 hp 415V without float switch, max 23.6 m h, 2400 l/m	5642.00


Note 1. requires ZEN-23.331 Ring Stand for free standing operation


Note 2. requires ZEN-23.180 Ring Stand for free standing operation




shown with ring stand



PART NO.	Description	LIST PRICE	Illustration
GRN - GRINDER			
Heavy duty cast iron submersible grinder pumps suitable for commercial applications. Grinding system can finely chop solids and fibres even under heavy duty conditions. This model has been redesigned featuring new electrical and mechanical parameters to optimise efficiency and reliability even under particularly heavy duty operation conditions. Pair of oblique ball bearings, are sized to guarantee 20,000 hours of operation. Two opposite mechanical seals both located in the oil sump. A special threaded bushing enables quick maintenance. Cable clamp with GAS thread, set up for cable ducting. 10m H07RN-F power cable. IP68 protection. 12 Months ZENIT PUMP Warranty * Parts and Labour			
ZEN-GRN250/2/G40HT	1.8 kW, 2.4 hp 415V without float switch, max 27.5 m h, 360 l/m Note 1	2923.00	
ZEN-GRN300/2/G50HT	2.2 kW, 3.0 hp 415V without float switch, max 32.0 m h, 360 l/m Note 1	3104.00	
ZEN-GRN400/2/G50HT	3.0 kW, 4.0 hp 415V without float switch, max 35.5 m h, 360 l/m Note 1	3919.00	
ZEN-GRN550/2/G50HT	4.1 kW, 5.5 hp 415V without float switch, max 46.2 m h, 360 l/m Note 1	4157.00	
ZEN-23.331	RING STAND	67.00	
Note requires ZEN-23.331 Ring Stand for free standing operation			

MAC MONO-CHANNEL - ANTI-CLOGGING			
12 Months ZENIT PUMP Warranty * Parts and Labour			
ZEN-MAN300/2/G65VT	2.2 kW, 3.0 hp 415V without float switch, max 20.6 m h, 900 l/m Note 1	2621.00	
ZEN-MAN300/2/80T	2.2 kW, 3.0 hp 415V without float switch, max 23.3 m h, 1260 l/m Note 1	2778.00	
ZEN-MAN400/2/80T	3.0 kW, 4.0 hp 415V max 21.1m h, 1260 l/m Note 2	3565.00	
ZEN-MAN550/2/80T	4.1 kW, 5.5 hp 415V without float switch, max 30.2 m h, 1620 l/m Note 2	3800.00	
ZEN-23.331	RING STAND	67.00	
ZEN-23.180	RING STAND	212.00	
Note 1. requires ZEN-23.331 Ring Stand for free standing operation			
Note 2. requires ZEN-23.180 Ring Stand for free standing operation			

AP HIGH HEAD			
12 Months ZENIT PUMP Warranty * Parts and Labour			
ZEN-APS100/2/G40HMGSIC	0.9 kW, 1.2 hp 240V with float switch, max 20.0 m h, 300 l/m	1749.00	
ZEN-APS100/2/G40HTSIC	0.9 kW, 1.2 hp 415V without float switch, max 20.0 m h, 300 l/m	1664.00	
ZEN-APE200/2/G50HMGSIC	1.7 kW, 2.3 hp 240V with float switch, max 29.0 m h, 500 l/m	2261.00	
ZEN-APE200/2/G50HTSIC	1.7 kW, 2.3 hp 415V without float switch, max 29.0 m h, 500 l/m	2173.00	
ZEN-APN300/2/G50HT	2.2 kW, 3.0 hp 415V without float switch, max 25.7 m h, 600 l/m Note 1	2822.00	
ZEN-APN400/2/G50HT	3.0 kW, 4.0 hp 415V without float switch, max 33.7 m h, 480 l/m Note 1	3606.00	
ZEN-APN550/2/G50HT	4.1 kW, 5.5 hp 415V without float switch, max 37.7 m h, 480 l/m Note 1	4879.00	
ZEN-APP750/2/G50HT	7.2 kW, 9.5 hp 415V without float switch, max 52.0 m h, 660 l/m	6490.00	
ZEN-23.331	RING STAND	67.00	
Note 1. requires ZEN-23.331 Ring Stand for free standing operation			







PART NO.	Description	LIST PRICE	Illustration
ACCESSORIES			
DAB-DSD2	Lifting Device Kit	372.00	 <p>CF Bracket</p>  <p>CF50V</p>  <p>NRV</p>
ZEN-CFBALL50V	Coupling Device C/W Ball NRV and Bleed, Vertical Outlet	716.00	
ZEN-CF50V	Coupling Device	481.00	
ZEN-CF65	Coupling Device with Vertical Outlet	622.00	
ZEN-CF80	Coupling Device with Vertical Outlet	702.00	
ZEN-CF100	Coupling Device with Vertical Outlet	787.00	
ZEN-NRVBALL32	Ball Type Non-Return Valve	211.00	
ZEN-NRVBALL40	Ball Type Non-Return Valve	255.00	
ZEN-NRVBALL50	Ball Type Non-Return Valve	312.00	
ZEN-NRVBALL65	Ball Type Non-Return Valve	380.00	
ZEN-NRVBALL80	Ball Type Non-Return Valve	549.00	
ZEN-NRVBALL100	Ball Type Non-Return Valve	713.00	
ZEN-CABLE2G1	Cable H07 RNF	14.00	
ZEN-CABLE3G1	Cable H07 RNF	10.00	
ZEN-CABLE4G1.5	Cable H07 RNF	12.00	
ZEN-CABLE4G2.5	Cable H07 RNF	14.00	
ZEN-CABLE4G1.5+3G0.75	Cable H07 RNF	23.00	
ZEN-CABLE7G1.5+3G0.75	Cable H07 RNF	39.00	
ZEN-PN16-2	Flange 2" PN10	88.00	
ZEN-PN16-2.5	Flange 2-1/2" PN10	102.00	
ZEN-PN16-3	Flange 3" PN10	132.00	
ZEN-PN16-4	Flange 4" PN10	132.00	





PUMPS


PART NO.	Description	LIST PRICE	Illustration
RAINSAVER			
RAIN WATER HARVESTING SYSTEMS			 Rainsaver MKIII
*All surface mounted pumps are fitted with a 10M low level float kit Note: All pumps incorporate independent pump control auto restart & loss of prime protection			
SURFACE MOUNTED PUMP PACKAGES			
RS3-INOX60PCA	Rainsaver MKIII & BIA-INOX60PCA Stainless Steel Electronic Pump 4 Taps, 320 kPa, 36 lpm 2 Year BIANCO Pumpz & Rainsaver MKIII Infield Warranty Discount Code: BIA	618.00	 Inox 60 Multi 900
RS3-MULTI900PCA	Rainsaver MKIII & BIA-MULTI900PCA Stainless Steel Multistage Electronic Pump 9 Taps, 352 kPa, 80 lpm 2 Year BIANCO Pumpz & Rainsaver MKIII Infield Warranty Discount Code: BIA	768.00	
Note: (Bianco Pressure Systems) Taps show above have been calculated at 8 litres per minute			
RS3-JETCOM82MAPCX	Rainsaver MKIII & DAB-JETCOM82MAPCX Technopolymer Electronic Pump 6 Taps, 460 kPa, 60 lpm 2 Year DAB Pump & Rainsaver MKIII Infield Warranty Discount Code: DBP	908.00	 Jetcom
RS3-JINOX82MAPCX	Rainsaver MKIII & DAB-JINOX82MAPCX Stainless Steel Electronic Pump 6 Taps, 460 kPa, 60 lpm 2 Year DAB Pump & Rainsaver MKIII Infield Warranty Discount Code: DBP	990.00	
RS3-EUROINOX30/50MAPCX	Rainsaver MKIII & DAB-EUROINOX30/50MAPCX Stainless Steel Horizontal Multistage Electronic Pump 8 Taps, 413 kPa, 80 lpm 2 Year DAB Pump & Rainsaver MKIII Infield Warranty Discount Code: DBP	1194.00	 Euroinox
RS3-EUROINOX40/80MAPCX	Rainsaver MKIII & DAB-EUROINOX40/80MAPCX Stainless Steel Horizontal Multistage Electronic Pump 11 Taps, 577 kPa, 120 lpm 2 Year DAB Pump & Rainsaver MKIII Infield Warranty Discount Code: DBP	1424.00	
Note: (DAB Pressure Systems) Taps show above have been calculated at 10 litres per minute			
SUBMERSIBLE PUMP PACKAGES			
RS3-JH8003PMPGX	Rainsaver MKIII & BIA-JH8003PMPGX High Head Submersible Clean Water Pump Electronic Pump 8 Taps, 295 kPa, 80 l/min, 10m power cable 2 Year BIANCO Pumpz & Rainsaver MKIII Infield Warranty Discount Code: BIA	768.00	
RS3-DIVERTRON1200	Rainsaver MKIII & DAB DIVERTRON1200 Multistage technopolymer submersible pump Electronic Pump 9 Taps, 470kPa, 95 l/min, 15m power cable 2 Year DAB & Rainsaver MKIII Infield Warranty Discount Code: DBP	1200.00	
RS3-DIVER75MAPCX	Rainsaver MKIII & TES -DIVER75MAPCX Multistage Stainless Steel Submersible Pump Electronic Pump 8 Taps, 340kPa, 80 l/min, 10m power cable 2 Year TESLA & Rainsaver MKIII Infield Warranty Discount Code: TES	1298.00	

PART NO.	Description	LIST PRICE	Illustration
AUTOMATIC PRESSURE SYSTEMS			
TECHNOPOLYMER AUTOMATIC PRESSURE SYSTEM			
Fully Electronic, Comfortable Showers . Auto Restart, Automatically restarts after water loss or interrupted power . Dry Run Protection, Protects Pump from Damage . Eliminates Water Hammer, Protects Plumbing . Pre Assembled compact size for easy installation. Technopolymer Pressure System, 2 Year Bianco Pumpz Warranty			
BIA-TECH40PC	400W, 240V, Electronic Control, flows to 25 l/m, heads to 27 m 2 to 3 TAPS	249.00	
Note: The taps mentioned above have been calculated at 8 litres per minute			
BIANCO INOX AUTOMATIC PRESSURE SYSTEM			
Fully Electronic, Comfortable Showers. Auto Restart, Automatically restarts after water loss or interrupted power. Dry Run Protection, Protects Pump from Damage. Eliminates Water Hammer, Protects Plumbing. Pre Assembled compact size for easy installation. Stainless Steel Pressure System, 2 Year Bianco Pumpz Warranty			
BIA-INOX60PC	600W, 240V, Electronic Control, flows to 36 l/m, heads to 32 m 3 to 4 TAPS	319.00	
BIA-INOX80PC	800W, 240V, Electronic Control, flows to 43 l/m, heads to 40 m 4 to 5 TAPS	359.00	
BIA-INOX120PC	1200W, 240V, Electronic Control, flows to 50 l/m, heads to 50 m 5 to 6 TAPS	399.00	
Note: The taps mentioned above have been calculated at 8 litres per minute			
HORIZONTAL MULTISTAGE Pressure System Pumps			
Self Priming. Starts automatically when a tap is turned on. Operates constantly from low flow to full flow. Stops automatically when the last tap is turned off. Run dry protection. Corrosion resistant stainless steel construction. Auto restart controller, automatically looks for water if pump runs out of water. Ideal for: domestic water supply for holiday homes and cottages, irrigation and car washing General water transfer systems. Pressures up to 548 kPa (80psi) 2 Year Bianco Pumpz Warranty * Parts and Labour			
BIA-MULTI900PC	900W, 240V, Electronic Control, flows to 90 l/m, heads to 36 m 11 TAPS	469.00	
BIA-MULTI1300PC	1300W, 240V, Electronic Control, flows to 90 l/m, heads to 56 m 11 TAPS	519.00	
Note: The taps mentioned above have been calculated at 8 litres per minute			
PUMP COVER			
<u>COVER YOUR PUMPS FROM THE ELEMENTS</u>			
<i>To extend the working life of your pump it is recommended that all pumps be covered from the elements. To suit pumps fitted with electronic controllers</i>			
One size suits DAB or BIANCO Electronic Pumps. Sturdy 2 piece design – base and lid. Protects your pumps from the elements. Base keeps pump off the ground. Cut-out slots for inlet and outlet piping. Ventilation holes in base and lid. Lid screw-fixes to base to prevent child tampering Colour: Beige Length: 720mm, Width: 420mm, Height: 520mm			
WHI-PUMPCOVER	Pump Cover for Pumps	185.00	


PUMPS
**BIANCO
PUMPZ**

PART NO.	Description	LIST PRICE	Illustration
SUBMERSIBLE PUMPS			
Drainage Pumps (clean water)			 BIA-JH400  BIA-JH550
Suitable for all de-watering tasks including pumping out sumps, flooded areas and drawing water from wells. Domestic use only. Light and compact, fully automatic operation. Great Value for Money. 10m Cable, 12 Months Warranty Special features: <ul style="list-style-type: none"> • Simple installation • Instructions included • Light and compact • Fully automatic operation • Great value for money • Supplied complete with 10 metres of electric cable • 12 Months Warranty • Not suitable for construction sites, ponds, fountains or biotreatment. 			
BIA-JH400	400W, 240V, Plastic Construction, flows to 125 l/m, heads to 8 m	130.00	
BIA-JH550	550W, 240V, Stainless Steel Construction, flows to 150 l/m, heads to 7.5 m	183.00	
BIA-JH900	900W, 240V, Plastic Construction, flows to 225 l/m, heads to 9 m	165.00	
Drainage Pump			
<ul style="list-style-type: none"> • Float controlled automatic stop and start • Ergonomic carrying handle • Outlet fitting • 10 metre cable and plug • Maximum particle size 5mm • Mechanical seal • 12 Months Warranty 			
BIA-JH60068	600W, 240V, Stainless Steel Construction, flows to 220 l/m, heads to 8.5 m	168.00	
'Light' Construction Submersible Pumps			 
The pump is characterised by: <ul style="list-style-type: none"> • Corrosion resistant pump components. • Fully automatic operation. • Dual Mechanical Seal in oil bath, SIC/SIC, Carbon Ceramic. • Euretane coated semi vortex impeller allows pumping of suspended solids, sandy and stringy material. • Agitator on the end of the pump shaft helps prevent air locking and clogging. • Carry handle. • Versatile outlet connection. • 240V single phase motor with in-built auto reset thermal overload. • 10m of power cable. • 12 months warranty. 			
BIA-AHS05A	Flows to 220, Heads to 12m	591.00	
BIA-AHS10A	Flows to 350 l/m, Heads 18m	684.00	
BIA-LAYFLATKIT	Lay Flat Hose 20m	180.00	
Drainage Pump with Internal Float Switch (clean water)			
Light and compact submersible clean water pump. Supplied wired and ready to install. Ideal for pits confined spaces where floats do not work. Incorporates float on/off switch for manual and automatic level control. The pump has an internal float switch which will not foul and allows for installation in small sumps. (min size 260mm x 160mm x 330mm deep). When switched to manual mode, the scavenger type base allows pumping down to 5mm. Not suitable for construction sites, ponds, fountains or bio-treatment. Dimensions: 203 x 321mm. 12 Months Warranty			
BIA-JH40011	400W, 240V, Plastic Construction, flows to 125 l/m, heads to 8 m	127.00	

PART NO.	Description	LIST PRICE	Illustration
Vortex Pumps			
<p>(non abrasive liquids with soft solids in suspension ie: leaves and stringy materials) Vortex drainage pumps are designed to pump water with some organic</p> <ul style="list-style-type: none"> • Light and compact • Fully automatic operation <p>Vortex drainage pumps are designed to pump water with some organic. Capable of pumping non-abrasive solids in suspension up to 35mm particle size.</p> <p>Special features:</p> <ul style="list-style-type: none"> • Simple installation • Instructions included • Great value for money • Handle particles up to 35mm in size • Supplied complete with 10 metres of electric cable • 12 months warranty • Not suitable for construction sites, ponds, fountains or biotreatment 			
BIA-JH550B	550W, 240V, Plastic Construction, Vortex, flows to 158 l/m, heads to 7 m	143.00	
BIA-JH750B	750W, 240V, Stainless Steel Construction, Vortex, flows to 208 l/m, heads to 8 m.	205.00	
HIGH HEAD Drainage Pump (clean water)			
<p>Light and compact high head submersible clean water pump supplied wired and ready to install. The pump has sufficient pressure to operate as a pressure system pump when wired to a suitable pump controller. 12 Months Warranty.</p> <p>Not suitable for construction sites, ponds, fountains or bio-treatment systems. Designed specifically for drinking water.</p> <p>Special features:</p> <ul style="list-style-type: none"> High Head, flows to 83 l/m. Corrosion resistant body Fully automatic operation. Silicon Carbide Mechanical Seal High Head Pump for rainwater tanks and clean water only Motor with built in auto reset thermal overload Supplied complete with 10 metres of electrical cable Dimensions: 164 x 150 x 337mm 			
BIA-JH8003P	800W, 240V, High Head, flows to 83 l/m, heads to 30 m, 10m cable	260.00	
PRESSURE SYSTEM			
HIGH HEAD Drainage Pump (clean water)			
MPCX model includes SK13B prewired and mounted on a stainless steel wall bracket. Complete with cover.			
BIA-JH8003PMPCX	800W, 240V, High Head flows to 83 l/m, heads to 30 m Corrosion Resistant Body. Fully automatic operation Silicon Carbide Mechanical Seal motor with built in auto reset thermal overload, 10m cable	599.00	



PART NO.	Description	LIST PRICE	Illustration
----------	-------------	------------	--------------

POOL RANGE

Pool Pumps

The BIANCO range of pool pumps provides strong and quiet pumping performance in a compact, easy to install package.

- Self priming for ease of use.
- Constructed of strong corrosion and U.V. resistant materials for long and reliable working life.
- Powerful pumping performance delivers flow rates for rapid water turnover.
- Easy to remove, see through strainer lid allowing easy removal of debris.
- Large strainer basket allows long intervals between cleaning.
- 2m power lead with 10amp Australian three pin plug fitted to all models.
- Drain plug enables pump casing to be drained for easy maintenance.
- Heavy duty totally enclosed fan cooled double insulated motor.
- Electrically approved safe installation in the pool zone.
- Built-in thermal overload protects the motor against damage from overheating.
- Every unit is pressure and performance tested in factory ensuring quality and reliability.
- Barrel Unions included for ease of installation and service (FCP).
- High performance carbon ceramic mechanical seals for long life.
- Stainless steel motor shaft resists corrosion.
- Elevated pump mounting corrosion resistant base keeps moisture well away from the motor (FCP).
- Larger strainer basket to protect the pump and reduce frequent cleaning.

2 YEAR Bianco Pool Pump Warranty * Parts and labour
Electrical Approval No: NSW 23665


BIA-FCP370S

BIA-FCP1100S

BIA-CLP5001	500W, 240V, Flows to 150 l/m, heads to 10.0 m	163.00
BIA-FCP370S	370W, 240V, Flows to 215 l/m, heads to 12.5 m	308.00
BIA-FCP750S	750W, 240V, Flows to 290 l/m, heads to 15.1 m	350.00
BIA-FCP1100S	1100W, 240V, Flows to 500 l/m, heads to 17.0 m	587.00
BIA-FCP1500S	1500W, 240V, Flows to 550 l/m, heads to 18.5 m	637.00

Salt Water Chlorinators

- Smart micro-computer controlled system
- Easy to use menu driven navigation system
- Backlit Digital LCD display
- Backlit intuitive navigation buttons
- Precision adjustment of chlorine output to 1%
- Dynamic tracking locks to chlorine output settings for precise chlorine production
- Super Chlorinate Mode
- Low and High Salt indicators
- Audible Alert when remedial action is required
- Automatic power reduction upon high salt condition
- Pump Protection
- Spa Mode
- Battery backed clock
- Self cleaning cell - standard on all models
- Large cell surface area prolongs cell life
- Exceptionally high quality cell anode material assures high efficiency

12 MONTHS Warranty



BIA-SC20	20 g/hr Chlorine Production	1400.00
BIA-SC25A	25 g/hr Chlorine Production	1500.00
BIA-SC30	30 g/hr Chlorine Production	1630.00



Sand Filters		
<ul style="list-style-type: none"> Improved water flow with the ultra pure filtration. Corrosion and U.V. resistant polyester reinforced fibreglass winding design for exceptional strength which will not split. Resistance against chemicals and corrosion with the ability to withstand high temperatures. Barrel unions for ease of installation and serviceability. Top mount heavy duty 7 position including winterize multi-port valve with large easy to operate handle and built in waste port for inspection of backwash water. Standard stainless steel long life oil filled pressure gauge. Simple backwashing required periodically without need to hose down filter elements. Suitable for use with Zeolite filter media. Max. Water Temperature: 43° 10 YEAR WARRANTY ON TANKS 2 YEAR WARRANTY ON COMPONENTS 		
BIA-T21	192 l/m, 300 kPa, 85kg sand	448.00
BIA-T25	270 l/m, 300 kPa, 155kg sand	517.00
BIA-T32	420 l/m, 300 kPa, 210kg sand	1061.00









Cartridge Filters		
<p>High Performance cartridge filters are used to maintain a clean and safe swimming environment for your family in your pool or spa. Contaminants and debris are collected in the fine fibres of the cartridge element pleats. The cartridge element is easily removed from the filter tank for periodic cleaning, eliminating the need for backwashing of the filtration system.</p> <ul style="list-style-type: none"> Easy access to cartridge element via heavy duty lock ring. Auto pressure relief preventing damage to pump and filter should filter become blocked. Quick connect barrel unions for ease of plumbing. Choice of two inlet ports enables inlet to be installed at either 90 or 180 degrees to the outlet for installation versatility. No backwashing of filter required. Stainless steel long life oil filled pressure gauge. Compact, low profile UV resistant tank. <p>2 YEAR Bianco Pumpz Warranty * Parts and labour</p>		
BIA-AF25	183 l/m, 350 kPa, suits 370W Pump	370.00
BIA-AF25CART	Spare Cartridge	107.00
BIA-AF75	283 l/m, 350 kPa, suits 750W Pump	479.00
BIA-AF75CART	Spare Cartridge	148.00
BIA-AF150	400 l/m, 350 kPa, suits 1500W Pump	680.00
BIA-AF150CART	Spare Cartridge	189.00






HOT WATER CIRCULATOR		
<p>The pump is characterised by:</p> <ul style="list-style-type: none"> Materials of construction suitable for potable water. 3 speed operation for lower power consumption. Flows to 65 litres/minute, heads to 6m Quiet operation (< 45 dB(A)) <p>Pump performance: Max flows speeds 1, 2, 3: 20 l/m, 42 l/m, 65 l/m Max heads speedd: 1, 2, 3: 3m, 5m, 6m Liquid: Max. operating water temperature: 80°C, temperature: Class 110 Materials: Pump Body: Bronze, DR, Back Plate and Rotor Can: Stainless Steel. Impeller: PPO Installation: Max. ambient temperature: 40°C, Maximum operating pressure: 10 bar Port Spacing: 150mm, Pipe connections suction/discharge: 1 - 1/4" BSP M Optional Union Set: 1 - 1/4" BSP F/3/4" BSP F. Electrical Data: Rated voltage: 240V, Mains frequency: 50 Hz Current Max: 0.4 amps. Capacitor: 3 uF, Power consumption speeds 1, 2, 3: 46W, 67W, 100W. Motor duty: Continuous. Motor Type: Canned Rotor. Motor Protection: In-built thermal overload Ingress protection: IP 42. Insulation class: F. Power cable length: 1.2m. Net weight 4kg</p> <p>12 Months Warranty</p>		
BIA-LRS32-6CU	3 Speed Bronze Circulators complete with Unions	229.00
BIA-LRS32UNION3/4B	Pair of 3/4" Brass Unions	33.00





PART NO.	Description	LIST PRICE	Illustration
FIRE RANGE - ENGINE POWERED PUMPS			
BIA-HP15A	<p>5.5hp Fire Pump The pump is a compact self-priming engine driven fire pump which is also ideal for high general duty applications. Supplied ready to operate complete with hose fittings and suction strainer. Heads to 55 metres Flows to 330 l/min Suction to 7 metres 1 x 1-1/2", 2 x 1" BSP male discharge ports 1 x 1-1/2" BSP male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 12 Month Warranty</p>	703.00	
BIA-2HP15A	<p>5.5hp Twin Stage Fire Pump The pump is a compact self-priming engine driven Fire-pump supplied ready to operate complete with hose fittings and suction strainer. Heads to 75 metres Flows to 200 l/min Suction to 7 metres 1 x 1-1/2", 2 x 1" BSP male discharge ports 1 x 1-1/2" BSP male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 12 Month Warranty</p>	749.00	
BIA-WP20A	<p>5.5hp Tanker Pump The pump is a compact self-priming engine driven 2" Tanker Pump supplied ready to operate complete with hose fittings and suction strainer. Designed for tank filling, water carts and dust suppression. Heads to 30 metres Flows to 450 l/min Suction to 7 metres 1 x 2" BSP male discharge ports 1 x 2" BSP male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 12 Month Warranty</p>	571.00	
BIA-WP30A	<p>6.5hp GUSHER Pump The pump is a compact self-priming engine driven 3" Gusher Pump supplied ready to operate complete with hose fittings and suction strainer. Designed for rapid dewatering tasks and tank filling applications. Heads to 30 metres Flows to 1000 l/min Suction to 7 metres 1 x 3" BSP male discharge ports 1 x 3" BSP male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 12 Month Warranty</p>	670.00	

PART NO.	Description	LIST PRICE	Illustration
BIA-FTB50H	<p>5.5hp Fire 'Plastic' Pump With Honda Engine</p> <p>The pump is a compact self-priming engine driven Plastic pump supplied ready to operate complete with hose fittings and suction strainer for pumping approved industrial and agricultural chemicals.</p> <p>Heads to 30 metres Flows to 580 l/min Suction to 7 metres 1 x 2" male discharge ports 1 x 2" male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 2 Year Warranty</p>	\$1099.00	
BIA-HP15AH	<p>5.5hp Fire Pump With Honda Engine</p> <p>The pump is a compact self-priming engine driven Fire-pump supplied ready to operate complete with hose fittings and suction strainer.</p> <p>Heads to 55 metres Flows to 330 l/min Suction to 7 metres 1 x 1-1/2", 2 x 1" BSP male discharge ports 1 x 1-1/2" BSP male suction port Low Oil Level Engine Protection Roll Frame Rubber Mounting Feet 2 Year Warranty</p>	\$989.00	
BIA-WP10AA	<p>1.5hp Portable Engine Pump</p> <p>The pump is a light weight self-priming general duty engine driven pump. Supplied ready to operate complete with hose fittings and suction strainer.</p> <p>Heads to 22 metres Flows to 116 litres Suction to 7 metres 1" BSP female ports Carry Frame Rubber Mounting Feet 12 Month Warranty</p>	\$319.00	
BIA-FFHK	<p>Fire Fighting Hose Kit</p> <p>The Fire Fighting Hose Kit comprises of: 1 x 5m x 38mm grey PVC suction hose c/w strainer, nut and tails plus 2 x 10m x 20mm black fire fighting delivery hose c/w nozzles, nuts and tails.</p>	\$311.00	

PART NO.	Description	LIST PRICE	Illustration
AUTO REELS			
BIA-ZA01-20B	<p>20m AIR REEL 180° Swivel Rotation Includes 20m Hose & Fittings Convenient Carry Handle Automatic Rewind The Retractable Auto Hose Reel provides secure storage of your hose and allows you to extend and retract your hose without kinks and knots. 180° rotation extends your reach and allows you to reach all desired points within the hose length. The convenient carry handle enable you to move the hose reel between selected mounting points. 12 Months Warranty</p>	178.00	
BIA-ZW03-20B	<p>20m WATER REEL 180° Swivel Rotation Includes 20m Hose & Fittings Convenient Carry Handle Automatic Rewind The Retractable Auto Hose Reel provides secure storage of your hose and allows you to extend and retract your hose without kinks and knots. 180° rotation extends your reach and allows you to reach all desired points within the hose length. The convenient carry handle enable you to move the hose reel between selected mounting points. HOSE – 20 metre Internal Diameter – 12mm (1/2"), Max. Pressure-1.000kPa(150PSI), Temp Range -5° Deg/45° DegC Fittings: 3/4" NPT 12 Months Warranty</p>	177.00	
BIA-ZW05-30B	<p>30m WATER REEL The new BIA-ZW05-30B is a Retractable Auto Hose reel which provides secure storage of the 30 metres of hose supplied and allows the user to extend and retract the hose without kinks and knots. The hose is simply unwound to any desired length. The BIA-ZW05-30B features a special slow and steady automatic rewind mechanism with locking stop. The hose reel is characterised by: ·Hose unwinding to any desired length. ·Slow and steady automatic rewinding with stop. ·30 metre (100') hose length. ·1.7 metre supply hose with quick release coupling and 3/4" tap connector. ·Spray nozzle with jet adjustment. ·Easy disassembly and transport for winter storage. ·180° lateral pivoting. Liquid: Clean water temperature range: 0° – 45° C Hose: Length: 30m (100') Internal diameter: 12mm (1/2") Maximum pressure: 1000 kPa (150psi) 12 Months Warranty</p>	273.00	

PART NO.	Description	LIST PRICE	Illustration
D.C. PUMPS FOR DIESEL - 12 MONTH WARRANTY			
PIU-000335	BY-PASS 2000 12V	351.00	
PIU-000336	BY-PASS 2000 24V 40 l/m rotary self-priming vane pumps for diesel transfer. All models come complete with by-pass valve.	351.00	
PIU-000223	CARRY 2000 12V	484.00	
PIU-000224	CARRY 2000 24V 40 l/m rotary self-priming vane pumps for diesel transfer. All models come complete with by-pass valve, cables, clamps and switch.	484.00	
PIU-000225	BATTERY 2000 12V	621.00	
PIU-000225A60	BATTERY 2000 12V + AUTO NOZZLE	724.00	
PIU-000226	BATTERY 2000 24V 40 l/m rotary, self-priming vane pumps for diesel transfer. All models come complete with by-pass valve, cables, clamps, switch and Self 2000 nozzle.	621.00	
PIU-000218	DRUM 2000 12V	750.00	
PIU-000219	DRUM 2000 24V 40 l/m rotary self-priming pumps for diesel transfer. All models come complete with by-pass valve, cables, clamps, switch, 4m rubber hose and Self 2000 nozzle as well as telescopic drum spear and 2" drum coupling.	750.00	
PIU-000363-12V	BI-PUMP 12V	935.00	
PIU-000363-24V	BI-PUMP 24V 85 l/min, 1" ports	935.00	
FLOW METERS			
PIU-000550	K33 Volumetric meter for diesel fuel, 3 digits resettable 6 digits totaliser.	443.00	
PIU-000560	K44 Volumetric meter for diesel fuel, 4 digits resettable 8 digits totaliser.	605.00	


PUMPS


PART NO.	Description	LIST PRICE	Illustration
A.C. PUMPS FOR DIESEL - 12 MONTH WARRANTY			
PIU-000730	PANTHER 56 240V 56 l/m, 370W, 2900 rpm, 1" ports with filter	499.00	
PIU-000732	PANTHER 72 240V 72 l/m, 500W, 2900 rpm, 1" G Flanged with filter	613.00	
PIU-000305	E 80 240V 75 l/m, 500W, 1450 rpm, 1" ports	895.00	
PIU-000326	E 120 240V 100 l/m, 780W, 1450 rpm, 1" ports	1197.00	
PIU-000271	DRUM 56 240V 56 l/m, 370W, 2900 rpm, 1" ports with filter, cables, clamps and switch, 4m rubber hose and Self 2000 nozzle as well as telescopic drum spear and 2" quick drum coupling. Shown with optional K33 meter and automatic nozzle.	822.00	
PIU-000575	CUBE 56 240V 56 l/m, 370W, 2900 rpm, 1" ports with filter, cables and switch, 4m rubber hose and automatic nozzle hanger. Cube 56 is also applied with volumetric meter, 3 digits resettable and 6 digits totaliser, anti-corrosive treated steel painted cabinet.	1745.00	
NOZZLES			
PIU-000641	SELF 2000 MANUAL NOZZLE 1" BSP	65.00	
PIU-A60	AUTOMATIC NOZZLE A60 1" BSP	103.00	

PART NO.	Description	LIST PRICE	Illustration	
A.C. PUMPS FOR OIL - 12 MONTH WARRANTY				
ELECTRIC PUMPS				
PIU-000304300	VISCOMAT 230/3M 14l/min 16 bar 240V	1163.00		
PIU-000334	VISCOMAT 70M 25 l/min 6 bar 240V	959.00		
PIU-000331900	VISCOMAT 70T 25 l/m 6 bar 415V	959.00		
PIU-000303	VISCOMAT 90T 50 l/min 5 bar 415V	1044.00		
OIL EQUIPMENT				
K400 HOSE END METER				
PIU-000976	K400 CAL L/BSP +easy oil + swivel, without spout	782.00		
K450 HOSE END METER				
PIU-000688	K450 Meter Nozzle BSP without spout	877.00		
K500 PRESET BATCH METER				
PIU-000687	K500 Meter Nozzle BSP with spout	1814.00	 K 500	
OIL NOZZLE				
PIU-000966	Easy Oil FF - hand grip only 1/2" x 1/2" BSP	76.00		
PIU-00845600A	1/2" Oil Swivel	25.00		
SPOUT with Automatic Anti-Drip Valve for K400				
PIU-000665	Rigid Spout BSP A/P	66.00		
PIU-000666	Flexible Spout BSP A/P	87.00		
DUMBOXES				
PIU-000920000	Oil Containers 5 Litres	32.00		
PIU-000917000	Oil Containers 2 Litres	19.00		
PIU-000930000	Funnel 180mm	19.00		
PIU-000931000	Funnel 220mm	21.00		
K400 OVAL GEAR DIGITAL METERS				
PIU-000475	Meter K400 CAL L/BSP	580.00		


PUMPS
