

To: White International Pty Ltd

10-Mar-26

Sekisui Jushi Trading Co.,Ltd.

Certificate of Material Composition for GC-30NP

Product name: Glass fiber-filled convex(GC-30NP)

We hereby certify that the material composition of the above mentioned product is as follows:

1. Constituent Materials

ITEM	MATERIAL COMPOSITION
TAPE	FRP coated with Urethan resin
CASE	ABS resin
EDGE HOOK	Poly carbonate
STRAP	PVC resin

2. Insulation Test Results for Non-conductive measuring Tape

DRY CONDITION		WET CONDITION	
Withstand voltage	Leakage current	Withstand voltage	Leakage current
25kv(AC)	Below 100mA	25kv(AC)	Below 100mA

【Measurement】


- ① Place three electrodes at the center of the specimen tape(30cm in length), with a spacing of 10cm between them.
- ② Measurement was conducted by applying 25kv(AC)voltage for 60 seconds.

Test result: Passed

【Condition of Tape at the time of Testing】

- ◆ Dry condition:
- ◆ Wet condition: Under the environmental conditions of 15.8°C room temperature and 60.3% relative humidity, the specimen tape was soaked in tap water for 3 hours.
After removing surface water droplets, a 25kv AC voltage was applied for 60 seconds for measurement.

Sekisui Jushi Trading Co.,Ltd.


K. Kita, Manager