



WaterMark Level 1

Certificate of Conformity

Australian Certification Services Pty Ltd grants to the WaterMark User:

White International Pty Ltd

Trading as White International Pty Ltd

the right to use the WaterMark as shown above in conjunction with the Certificate No. on product/s as identified in the WaterMark Schedule and as listed on the WaterMark database www.abcb.gov.au/product-certification which have been shown to comply with the relevant Standard/s and level of certification referred to below. The WaterMark User is granted a licence to use the WaterMark subject to the rules governing the use of the WaterMark.

Product Type: Rainwater/Mains Supply Changeover Device
Evaluated to: ATS 5200.477:2006 Technical Specification for plumbing and drainage products
Part 477: Rainwater/Mains Supply Changeover Device

Paul Greig
General Manager

Issue Date: 21st October 2016
Initial Issue Date: 24th July 2009
Expiry Date: 23rd July 2019

Certificate No.: 23022

This certificate remains the property of Australian Certification Services Pty Ltd

WaterMark Level 1 certification is a conformity assessment scheme based on ISO Guide 67 (system 5)





WaterMark Certification Schedule

The WaterMark User	White International Pty Ltd ABN: 48 000 119 380 52-60 Ashford Avenue, Milperra, NSW 2214 AUSTRALIA Website: www.whiteint.com.au
Certificate Number	23022
Level of Certification	WaterMark Level 1
Certification Standards:	ATS 5200.477:2006 Technical Specification for plumbing and drainage products Part 477: Rainwater/Mains Supply Changeover Device

Product Listing

Model Identification	Model Name	Brand Name	Product Description
Bia-Rainsaver Mk3	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device for use with self prime pumps Max Operating Pressure/Temperature 800kPa/40°C Max Flow rate 100L/min
Bia-Rainsaver Mk3E	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device for use with self prime pumps Max Operating Pressure/Temperature 800kPa/40°C Max Flow rate 100L/min Electric version
Bia-Rainsaver Mk5	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device to be Used in Conjunction with Rainsaver Pump Packages Max Operating Pressure/Temperature 1000kPa/40°C Max Flow rate 120L/min (Pump) 40L/min (Mains)
Bia-Rainsaver Mk4E	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device for use with self prime pumps Max Operating Pressure/Temperature 800kPa/40°C Max Flow rate 100L/min Electric version
Bia-Rainsaver Mk6-200kPa	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device to be Used in Conjunction with Rainsaver Pump Packages Max Operating Pressure/Temperature 1000kPa/40°C Max Flow rate 120L/min (Pump) 40L/min (Mains) 200kPa Set Pressure



Model Identification	Model Name	Brand Name	Product Description
Bia-Rainsaver Mk6-300kPa	Rainsaver	Rainsaver	DN20 Rainwater/Mains Supply Changeover Device to be Used in Conjunction with Rainsaver Pump Packages Max Operating Pressure/Temperature 1000kPa/40°C Max Flow rate 120L/min (Pump) 40L/min (Mains) 300kPa Set Pressure

AUSTRALIAN CERTIFICATION SERVICES

