



This pump is a domestic submersible water pump supplied wired and ready to install. Ideal for drainage of clean water in small pits where an external float switch will not operate. Incorporates a float on/off switch for manual or automatic level control.

When in manual mode, the scavenger type base allows pumping down to 5mm.

The pump is characterized by:

- Fully automatic operation with internal float switch
- Ideal for operation in small pits where external floats do not work
- 240V single phase motor with built-in auto reset thermal overload.
- 10m power cable
- Not suitable for construction sites, ponds, fountains or bio-treatment.
- Flows up to 118 l/m
- Max head 7m

Electrical data:

- Rated voltage: 240V
- Mains frequency: 50Hz
- Rated output: 400W
- Current: 2 amps
- Capacitor: 10µF
- Motor duty: Continuous
- Motor type: Asynchronous
- Motor protection: Built-in thermal overload
- Ingress protection: IPX8
- Insulation class: F
- Power cable length: 10m H07RNF
- Gross weight: 5 kg
- Carton dimensions: 220 x 180 x 340mm
- Maximum submergence: 5m

12 MONTHS BIANCO Pumpz Warranty

Also Available,
BIA-JH400S2, BIA-JH8003S2,
BIA-JH550BS2

Liquid:

Clean water temperature range: 2-35°C

Materials:

- Pump body, Impeller, Strainer: ABS
- Shaft Seal: Mechanical seal
Carbon / Ceramic
- O rings: Nitrile

Installation:

- Maximum liquid temperature: 35°C
- Discharge connection: 1.1/2" BSPM
(additional fittings provided in carton)

BIA-JH40011S2

