



The pump is a submersible water pump supplied wired and ready to install.

It is capable of pumping water with some organic content / non abrasive solids in suspension up to 35mm particle size

The pump is characterised by:

- Fully automatic operation.
- 240V single phase motor with in-built auto reset thermal overload.
- 10m of power cable.
- Flows up to 200 l/m
- Max head 7.5m

Liquid:

Clean water temperature range: 2-35°C

Materials:

- Pump body, impeller: ABS
- Shaft Seal: Mechanical seal
Carbon / Ceramic
- O rings: Nitrile

Installation:

- Maximum liquid temperature: 35°C
- Maximum submergence: 5m.
- Pipe connections discharge: 1-1/2" BSPF

Electrical data:

- Rated voltage: 240V
- Mains frequency: 50 Hz
- Rated output 550W
- Current: 3 amps
- Capacitor: 8 µF
- Motor duty: Continuous
- Motor type: Asynchronous, TEFC
- Motor protection: Built in thermal overload,
- Ingress protection: IPX8
- Insulation class: F
- Power cable length: 10 m H07RNF
- Net weight: 5.1 kg
- Pump carton dimensions: 220 x 180 x 420mm

12 MONTHS BIANCO Pumpz Warranty

Also Available:

- BIA-JH400S2, BIA-JH400I1S2,
- BIA-JH8003S2

BIA-JH550B2

