



AUTOTRONIC 25 BOOST 230V 12V/24V



Overview

AUTOTRONIC 25 BOOST 230V 12V/24V

cod. 807540

Battery charger with electronic control of the charging current, automatic interruption and restart (TRONIC), for charging lead-acid batteries with 12/24V voltage.

Fit with switches to choose either anormal charge (MIN) or quick charge (BOOST) in the buffer mode (TRONIC) or drooping characteristic mode (CHARGE).

The buffer automatic charge is adequate for maintenance free sealed batteries (GEL/AGM/START-STOP), while the drooping characteristic charge is adequate for free-electrolyte batteries (WET).

Features:

- choice of output voltage, type of charge, charging mode
- display of charging current
- protection against overloads and polarity reversal.



1 PH 230V



TRACTOR




EAC CERTIFICATION



CAR



VAN



TÜV SUD CERTIFICATION



BOAT



CE MARKING

Technical data



CODE 807540



EFFECTIVE CHARGING CURRENT 18 / 12 A



DIMENSIONS 22,5 - 29 - 20,5 cm



AUTOTRONIC 25 BOOST 230V 12V/24V

SINGLE PHASE MAINS VOLTAGE 230 V	RATED CHARGE CURR. EN60335-2-29 12 / 8 A	WEIGHT 7,2 kg
MAINS FREQUENCY 50 - 60 Hz	MIN. RATED REFERENCE CAPACITY 30 / 20 Ah	EAN CODE 800489764142 3
CHARGING ABSORBED POWER 300 W	MAX RATED REFERENCE CAPACITY 225 / 180 Ah	PIECES/PALLET 56 pz/pallet
CHARGING VOLTAGE 12 / 24 V	ADJUSTMENT POSITIONS 4	PIECES/PALLET - B 42 pz/pallet - B

Included Accessories

COLORADO 40B WORK CLAMP 40A - 712624	POSITIVE CABLE 2,5 MMQ 1,5 M - 123986
COLORADO 40R POSITIVE CLAMP 40A - 712623	WORK CABLE 2,5 MMQ 1,5 M - 123985