E.SYTWIN TECHNICAL INFORMATION



GENERAL DESCRIPTION

DAB Pumps are proud to officially launch the second phase of our brand new innovative booster product to the market, leading the way in electronic pump technology.

The E.SYTWIN is a completely new solution in cold water boosting for residential and light commercial applications.

Essentially a twin pump, water cooled booster pump with integrated high efficiency variable speed motor,

But the e.sytwin offers much more.... please see our commercial documentation for full pump details.

DESIGN FEATURES

- Water cooled motor and sound dampening casing creating the quietest booster pump available today
- Energy efficient variable speed motors operating from 0.25 KW to 1.5 KW
- Powerful performance Flow up to 3.3 Litres/second and head up to 6 Bar
- Self priming down to 5 Metres
- · Dry running protection
- Frost protection
- Anti-vibration mountings
- · Integrated chambers with expansion vessels, tool kit and installer manual
- Wireless connectivity and modular design can expand the pump system up to a 4 pump booster set




E.J.L.T.MIJ

TECHNICAL DATA

MODEL	VOLTAGE	FREQUENCY	CONNECTION SIZE		ELECTRICAL DATA			
			SUCTION	DISCHARGE	MAX	MAX	PROTECTION	MOTOR
					Α	POWER	CLASS	CLASS
e.sytwin	220-240 V / 1 ~	50/60 Hz	1 ¼" BSP F	1 ¼ " BSP F	2 x 10 AMP	2 x 1550 W	IP44	F

PERFORMANCE



OVERALL DIMENSIONS			WEIGHT	MAX WORKING	MAX LIQUID	MAX WORKING	
L	L W H		EMPTY	PRESSURE	TEMPERATURE	ENVIRONMENT	
753 mm	352 mm	729 mm	66 KG	8 Bar	+ 40 ° C	+ 50 ° C	

INTEGRATED SYSTEM PROTECTION INCLUDES:


- Protection against dry running (Auto & manual reset options)
- Antifreeze protection
- Anticyling protection
- Motor overload protection
- Protection against abnormal supply voltages
- Protection against excessive temperatures

Maximum Flow: 200 Litres/Minute Maximum Head: 60 Metres Priming: 5 Mins at 5 Metres

Part No: DAB-E.SYTWIN Item Code: 801121



E.SYTWIN DIMENSIONS





⋿∵८┟┸⋒Ӏ┚

