







Liquid: Liquid Type: Clean Water

Clean water temperature range: 2 - 35° C

Materials:

Pump Body: Aluminium Impeller: Aluminium

 $\textbf{Mechanical Seal:} \ \mathsf{Carbon/Ceramic/Nitrile}$

O rings: Nitrile

Installation:

Maximum ambient temperature: 40°C Self Priming Time at 5m: <120 seconds

Weight:

14.5kg

Engine Data:

Type: Single Cylinder, Aircooled, 4 Stroke OHV

Model: G87 HP gross: 3.0

Displacement: 87 cc **Air Cleaner:** Dual Element,

Paper and Foam Ignition: CDI Starting: Recoil Fuel Capacity: 1.8 Litre Oil Capacity: 0.35 Litre

30 25 25 26 27 20 20 20 20 20 20 20 20 30 30 30

BIANCO VULCAN 3.0 HP PORTABLE PETROL ENGINE PUMP

The pump is a light weight self priming engine driven pump supplied ready to operate with hose fittings and suction strainer.

The pump is characterised by:

- Single Cylinder, 4 Stroke,
 Forced Air Cooled OHV Engine
- Heads to 25 metres
- Flows to 300 l/min
- Suction to 8m
- 1-1/2" BSP Male Discharge Port
- 1-1/2" BSP Male Suction Port
- Carry Frame
- Rubber Mounting Feet

Features:

- · Custom Built Frame
- Spark Arrester
- Full Serviceability Without Removing Pump from Frame

Applications:

- Dust Suppression
- Water Transfer
- Tank Filling
- De-watering



