

FlowThru™ Inline Adaptor

The FlowThru™ Inline Adaptor from Global Water Solutions is compatible with GWS inline tanks with 1" connections.

Particularly useful for use with VFD controlled pumps, the FlowThru™ inline adaptor is uniquely designed to ensure maximum circulation in the tank while assuring low pressure drop in the main pipe. The fitting easily mates with the tank and the insert redirects water through the pressure tank, eliminating the possibility of stagnant water during normal system operation.

Featuring multiple orientations for installation, it eliminates the risk of leaking or overtightened connections.



Key features and specifications:

- Patent Pending FlowThru™ Technology, ensuring Recirculation in the tank for the freshest water.
- Reduces the risk of water-borne diseases like Legionnaires disease.
- Flexible installation orientation.
- Maximum working pressure: 25 bar / 362 psi.
- Maximum temperature: 85° C / 185° F.
- Fitting material: 304 stainless steel.
- Insert material: Noryl.
- Available with 1" BSP connection (IFA-100BSP).
- Available with 1" NPT connection (IFA-100NPT).

Compatible with Global Water Solutions inline tanks with 1" BSP or NPT connection including:

- PressureWave™ 2-35 litre inline tanks.
- Max™ 2-35 litre inline tanks.
- UltraMax™ 8 and 24 litre inline tanks.
- M-Inox™ 8 - 24 litre inline tanks.
- All-Weather™ 18 and 24 litre inline tanks.

