

Receiver
From

 Society
 Reference
 Address
 Phone
 Fax
 E-mail

Motor Code :

60168919

Motor :


4OL 1,5 kW 230 V M

Materials

Internal sleeve and outer casing	Stainless Steel AISI 304 L
Upper support	Nickel-plated cast iron
Shaft extension	Stainless Steel AISI 304/Duplex
Bearing cover	Stainless Steel AISI 304
Mechanical seal	Carbon/Ceramic
Gasket	NBR
Lower cover	Stainless Steel AISI 304
Bellow seal	EPDM
Dowels	Stainless Steel AISI 304
Cable	EPDM
Connector plug	Stainless Steel AISI 316
Sand guard (fixed-mobile)	NBR
Screws	Stainless Steel AISI 304
Coolant	Mineral oil

Motor data

Motor brand :	TESLA	
Nominal power P2 :	1.5 kW	
Rated speed :	2800 1/min	
Rated voltage :	1~ 230 V	50 Hz
Nominal current :	10.8 A	
Degree of protection :	IP 68	
Inverter application :	Allowed - min. 30Hz	
Power factor :	0.87	
Efficiency :	69 %	
Cable section Ø mm ² :	4x1,5	
Cable length m :	1,7	
Cooling flow :	min. 0,3 m/s at 35°C	


Weight : 11.7 kg

Dimensions in mm

L	400				