

Submersible Pressure Pump BLUEDIVER

- Compact
- Auto on/off Float Switch
- Overheating Protection
- Stainless Steel Filter
- 🇮🇹 Designed in Italy

3
YEAR
WARRANTY



**Adjustable
Float**



**Stainless Steel
Filter**



Float



	Model	BLUEDIVER C30	BLUEDIVER C40
Electrical data	P1 Power consumption [W]	900	1.100
	P2 Pump consumption [W]	650	750
	Voltage [V]	1 ~ 220-240 AC	1 ~ 220-240 AC
	Frequency [Hz]	50	50
	Current [A]	3.8	4.8
	Capacitor μ F	12.5	12.5
	Capacitor Vc	450	450
	Rated speed [1/min]	2.850	2.850
Hydraulic data	Flow rate max. [l/min]	95	95
	Max. Pressure [Bar]	3.6	4.6
	Max. Head [m]	30	46
	Max. working pressure [bar]	6	6
	Max depth of immersion [m]	12	12
Range of use / materials	Length of Power Cable [m]	15	15
	Cable	H07 RNF	H07 RNF
	Pump International protection	IPX8	IPX8
	Insulation Class	F	F
	Liquid range Temperature [°C]	0 °C / +35 °C	0 °C / +35 °C
	Dimension of particles [mm]	clean water	clean water
	Max. Ambient Temperature [°C]	+40 °C	+40 °C
Dimensions / weight	L x W x H [mm]	150 x 150 x 400	150 x 150 x 400
	DNM GAS	1" F	1" F
	Box Dimensions l x w x h [cm]	23 x 19 x 46	23 x 19 x 46
	Net/Gross Weight [kg]	8.7/10	9/10.2
	Quantity for pallet [no.]	40	40

Max Head
(m)

