

PRODUCT DATA SHEET

CMS 1240A1 • 807734



BRAND



PRODUCT DETAILS

ClayTech Management Systems (CMS) provide the convenience of automatic selection between your water tank and mains supply, with the emphasis on maximizing the use of your rain water, with no power or additional wiring required..

BENEFITS

- Self priming enables the pump to draw reliably from water lower than the pump inlet
- High flow, flat consistent performance curve.
- Complies with AS/NZS 4020 requirements

FEATURES


- Multi-stage pump
- Quiet, reliable operation
- Designed for larger homes
- Self-Priming
- Automatic Operation - adjustable start pressure
- Controller includes a pressure gauge
- Inbuilt dry run protection

TECHNICAL DATA

P1 RATED POWER (W)	720W
MAX. FLOW [LPM]	100 lpm
MAX. HEAD [M]	48m
WORKING TEMPERATURE	< 40°C
LIQUID TEMPERATURE	2°C - 35°C
MAX. WORKING PRESSURE	6 Bar
MOTOR DUTY	S1 Continuous
MOTOR PROTECTION LEVEL	Class F
PUMP BODY	Technopolymer
DIFFUSER MATERIAL	Technopolymer
MOTOR PROTECTION	In-built auto re-setting thermal overload
CAPACITOR	12.5 uF +/-5% 450V

RATED VOLTAGE	220V-240V 50 Hz
RATED CURRENT	3.9A @ 230V
POWER CABLE TYPE	2m H07RN-F
PROTECTION CLASS	IPX4
INLET	1" BSPF
OUTLET	1" BSPF
MECHANICAL SEAL	Carbon/Ceramic
MOTOR SHAFT	Stainless Steel
IMPELLER MATERIAL	Stainless Steel
AUTOMATION FUNCTION	No - bare pump only
NET WEIGHT (KG)	Pump only 13.0 kg
PACKAGE DIMENSION	570Lx270Wx350H (mm)


HYDRAULIC PERFORMANCE



DIMENSIONS

INLET / OUTLET

1" BSPF



CMS SPECS



Max Mains pressure 1050kPa

Max Pump Pressure 1050kPa

Max flow 200LPM

Inlet/Outlet 1" BSPF

Weight 1.9kg



DIMENSIONS

Pump Only: 500 mm long, 220 High, 215mm wide

With controller: 450mm high

BASE FOOT

170 mm long, 275mm wide

WARRANTY / CERTIFICATIONS

