

TREATS UP TO 75,000L



**TANKCLENZ
TEST STRIPS**

810433

PRODUCT DETAILS

Bianco NXT Hydrashield 'Tankclenz' is a hydrogen peroxide-based disinfectant for use in stored drinking water supplies. The formulation is a chlorine-free, long-lasting and highly effective solution to ensure safe, clean water for you and your family. It breaks down into oxygen and water, making it both safe and eco-friendly.

APPLICATIONS

- Safe, effective disinfection for rainwater tanks
- Cleaning/disinfecting pipework
- Treating smelly water tanks
- Can be used to disinfect other water sources under advisement

FEATURES

- Protects stored water from bacteria and viruses for up to 2 months
- Perfect for treating drinking water tanks
- Chlorine-free disinfectant for rainwater tanks
- Kills 99.9% of bacteria & viruses
- No taste, odour or nasty by-products
- Treats up to 75,000L

STORAGE

- Store in original container with vented cap.
- Keep in a well-ventilated area away from direct sunlight and sources of heat.
- Store away from reducing agents and alkalis.

Active ingredients: 7.5% Hydrogen Peroxide, <0.01% Silver

For more information, scan on-pack QR code for safety data sheet.

TECHNICAL DATA

SPECIFICATIONS

PRODUCT TYPE	Drinking Water Disinfectant
SUITABILITY	Rainwater Tanks
FORMULATION	Silver-stabilised Hydrogen Peroxide
NET VOLUME	5L

Hydrogen Peroxide is used as an antiseptic, a bleaching agent, or as an oxidiser. Hydrogen peroxide is simply water (H₂O) plus an extra oxygen atom (giving H₂O₂). The extra oxygen atom oxidises contaminants, which kills germs, leaving disinfected water.

The hydrogen peroxide concentration of Hydrashield Tankclenz (7.5%) is sufficient to be effective against waterborne nasties, but safe for you to handle and use.

The silver component helps stabilise the product, enabling ongoing protection for up to 2 months after dosing.

DOSAGE

VOLUME OF WATER TO BE TREATED (L)	SHOCK DOSE (30PPM)	MAINTENANCE DOSE (10PPM)
1,000	200ml	67ml
5,000	1L	334ml
10,000	2L	667ml
15,000	3L	1L
25,000	5L	1.7L
30,000	6L	2L
60,000	12L	4L
100,000	20L	6.7L
250,000	50L	16.7L