



PRODUCT DETAILS

The TS20STDRT 10-Micron Pleated Cartridge is commonly used as primary filtration for sediment, as it can be cleaned and reused to extend its service life.

50- and 20-micron versions are often used as the first in a series of filters, including as the primary filter in UV kits. Pleated cartridges have a large surface area to accommodate high flows with little pressure drop.

SPECIFICATIONS

CARTRIDGE SIZE	20" Standard
CONFIGURATION	SX — Double Open End
NOMINAL FILTRATION	10 micron
FILTER MEDIUM	Pleated polyester fabric
RECOMMENDED FLOW RATE	≤ 67 l/min
OUTER DIAMETER (OD)	70 mm (2.4")
INNER DIAMETER (ID)	30 mm (1.1")
LENGTH	505 mm (20")
WORKING TEMP	4 deg C - 45 deg C
COUNTRY OF ORIGIN	Italy


FEATURES & BENEFITS

- 10-micron nominal filtration reduces sediment, silt, sand, rust and suspended particulates
- Pleated polyester media provides a large filtration surface area for high flow rates
- Low pressure drop helps maintain system performance
- Washable and reusable design extends cartridge service life, with durable polypropylene core and end caps
- Double open-end (DOE) configuration – fits 20" standard housings

Flow Rate vs Pressure Drop Δp

Tests carried on 10" elements type **TS10SX**.

Testing mode: 20°C, 3 BAR



MAINTENANCE

Replacement interval depends on source water quality and flow rate.

Replace filters every 12 months OR when the difference between inlet and outlet pressure approaches 1 bar (pressure drop) with water running.