

PRODUCT DATA SHEET

WELLING AND CROSSLEY WC-P8750RCD 813072









MORILE BUSINESS



AGRICIII TIIRE





Total harmonic distortion 6 - 8%





The Welling and Crossley P8750RCD is a powerful AVR (Automatic Voltage Regulated) petrol generator equipped with convenient electric start and RCD (Residual Current Device) for protection against electrical faults. Supplied with transport kit (handles and wheels), this generator features a generously sized 25L fuel tank and economical motor, providing reliable, clean, and consistent power for running multiple appliances over extended periods.

APPLICATIONS

- Compliant with safety regulations for work areas and construction sites
- DIY workshops to power small to medium tools and
- Off-grid solar pumping system back-up
- Power irrigation systems, agricultural machinery
- Outdoor events for lights, sound systems etc
- Mobile businesses or market stalls for powering small appliances
- Not for use with equipment with built-in RCD protection

FEATURES

- 2 x IP66 Outlets (single phase 15 Amp)
- Multiple start options: Recoil start, push-button electric start, wireless remote start, 2-wire remote start
- Transport kit included: Fold-out wheelbarrow style handle and large wheels
- Powerful & efficient: Air cooled OHV 4-Stroke engine with large fuel tank
- Digital V/F/T Display (Volts, Frequency, Time)
- Transistorised Ignition
- Low oil alarm, overload alarm, output indicator
- 2 year Welling and Crossley Warranty (battery excluded)

TECHNICAL DATA

MODEL RATING	8.75kVa with AVR
POWER FACTOR	0.8
MAX. AC OUTPUT	7000W
RATED AC OUTPUT	6800W Max 15 amp
RATED MOTOR SPEED	3000rpm
RATED VOLTAGE	230/240V AC 1 Ph / 50Hz
ENGINE MODEL	WC-420: Euro 5 emissions compliant
ENGINE TYPE	Single cylinder, 4 stroke, OHV air cooled petrol
DISPLACEMENT	420cc

OIL	1.1 litres SAE10W-30
SPARK PLUG	Torch F6TC, Champion RN9YC
NOISE LEVEL @ 7M	72 dBA
FUEL TYPE	Petrol – 91 octane unleaded.
FUEL TANK CAPACITY	25L
FUEL CONSUMPTION	Approx 1.48 L/Hr @ 1/4 load
PACKAGING (L X W X H)	710 x 535 x 590mm
PRODUCT (L X W X H)	700 x 660 x 600mm
DRY WEIGHT	90kg



Euro 5