



POWERED BY
MICROBAN[®]



813120



813119



MAINTENANCE

Replace filters when the difference between inlet and outlet pressure approaches 1 bar (pressure drop) when water is flowing.

PRODUCT DETAILS

The product combination in every Atlas Filtri SANIC DP kitset has been selected to target specific water-related issues.

This kitset provides 2-stage sediment reduction with Microban-infused polypun filter cartridges to reduce microbial growth in the filter cartridges. The first cartridge provides 25-micron coarse filtration; the second provides 5-micron fine filtration.

Suitable for small to medium dwellings, the rated flow for these filters is 42 l/min (nominal 0.1 bar pressure drop).

KIT COMPONENTS

- 10" BIG DP DUO SANIC moulded head and housings
- 10" BIG 25-micron polypun SANIC cartridge filter
- 10" BIG 1-micron polypun SANIC cartridge filter

TECHNOLOGIES

Microban silver-based technology is permanently integrated into SANIC products (housings AND filters) and remains active throughout their life cycle.

Microban reduces the growth of bacteria not only on the product surface but also inside the cartridge, keeping the filter cleaner at a microscopic level, down to each pore.

This extends the sanitary life of the filter cartridges and potentially reduces the rate of pressure drop.

SPECIFICATIONS

MAX PRESSURE	8 bar
MIN WATER TEMP	4 deg C
MAX WATER TEMP	45 deg C
INLET / OUTLET	1" BSP
DIMENSIONS MM	390(W) x 475(H) x 200(D)