



POWERED BY
MICROBAN



813122



813173



812621



MAINTENANCE

Replace filters when the difference between inlet and outlet pressure approaches 1 bar (pressure drop) when water is flowing.

Sanitary life of carbon block cartridges is MAX 12 months.

ScaleArmor® ROCK est. 24-month lifespan.

PRODUCT DETAILS

The product combination in every Atlas Filtri SANIC DP kitset has been selected to target specific water-related issues.

This kitset provides coarse sediment reduction followed by fine sediment and chlorine reduction, then an anti-scale prevention solution.

KIT COMPONENTS

- 20" BIG DP TRIO SANIC moulded head and housings
- 20" BIG 25-micron polypun SANIC cartridge filter
- 20" BIG 5-micron carbon block cartridge filter for taste, smell and chlorine reduction
- 20" BIG refillable ScaleArmor ROCK cartridge for the prevention of limescale formation

TECHNOLOGIES

Microban silver-based technology is permanently integrated into SANIC products and remains active throughout their life cycle. Microban reduces the growth of bacteria not only on the product surface but also inside the cartridge, keeping the filter cleaner at a microscopic level, down to each pore.

The carbon block cartridge reduces chlorine to manage taste and smell issues. This cartridge also achieves a final 5-micron sediment removal stage. Rated flow to achieve the ideal 30 seconds of contact time for chlorine reduction is 26.6 l/min. Rated capacity est. 310,400L (90% reduction @ 2ppm).

ScaleArmor® ROCK prevents limescale from forming while protecting pipes and surfaces. The special cartridge is refillable.

SPECIFICATIONS

MAX HARDNESS	500 ppm
MAX PRESSURE	8 bar
MIN WATER TEMP	4 deg C
MAX WATER TEMP	45 deg C
INLET / OUTLET	1" BSP
DIMENSIONS MM	590(W) x 735(H) x 200(D)