



POWERED BY
MICROBAN[®]



812005



811883



MAINTENANCE

Replace filters when the difference between inlet and outlet pressure approaches 1 bar (pressure drop) when water is flowing.

ScaleArmor® BLUES must be replaced MAX 6 months.

Sanitary life of carbon block cartridges is MAX 12 months.

PRODUCT DETAILS

The product combination in every Atlas Filtri SANIC DP kitset has been selected to target specific water-related issues.

This kitset provides sediment and chlorine reduction with anti-scale prevention incorporated.

Suitable for supplying a single drinking water outlet, the rated flow for this kit is 6.7 l/min.

KIT COMPONENTS

- 10" STD DP DUO SANIC moulded head and housings
- 10" STD 5-micron SCALEARMOR Blues cartridge
- 10" STD 0.15-micron filter with both activated carbon and an ultrafiltration membrane for reduction of bacteria, protozoa, chlorine, taste and odour

TECHNOLOGIES

Microban silver-based technology is permanently integrated into SANIC products and remains active throughout their life cycle. Microban reduces the growth of bacteria not only on the product surface but also inside the cartridge, keeping the filter cleaner at a microscopic level, down to each pore.

ScaleArmor® BLUES prevents limescale from forming while protecting pipes and surfaces. The special cartridge not only acts as an anti-scale agent, but also retains fine sediment.

The activated carbon block provides fine sediment filtration and reduction of chlorine, taste, odour (CTO), and volatile organic compounds (VOC) – the internal hollow-fibre membrane module for microfiltration. This cartridge removes the finest sediment and a major part of harmful bacteria (E. coli, Salmonella, V. cholerae, Legionella, Pseudomonas) and protozoan cysts (Giardia, Cryptosporidium).

SPECIFICATIONS

MAX HARDNESS	500 ppm
MAX PRESSURE	8 bar
MIN WATER TEMP	4 deg C
MAX WATER TEMP	45 deg C
INLET / OUTLET	3/4" BSP
DIMENSIONS MM	235(w) x 375(H) x 135(D)