



PRODUCT DETAILS

A high-flow capacity filter for treatment of challenging water at home.

ECOMIX® C reduces hardness, iron, manganese, organics and ammonium.

Large salt tank and low salt consumption provides several months of water treatment before the next salt refill.

FEATURES

- Manufactured in Belgium
- Reliable US-made Clack® CE valve
- Large salt capacity – up to 130 kg
- Attractive design

COMPONENTS

- Pre-programmed Clack® CE valve
- Cabinet enclosure
- 1035 media chamber
- 25L ECOMIX® C
- Brine well with safety float valve

CERTIFICATIONS

- NSF/ANSI 44
- NSF/ANSI/CAN 61
- NSF/ANSI/CAN 372
- Watermark Pending



INFLUENT WATER

HARDNESS	750 mg/L CaCO ₃
IRON	15 mg/L
MANGANESE	3 mg/L
CHEMICAL O₂ DEMAND	20 mg/L O ₂
AMMONIUM	4 mg/L
PREFILTRATION	≤100 µm
WATER TEMP	+4 to 30° C
PH	5 - 9
CHLORINE	≤1 ppm
TDS	≤4000

SPECIFICATIONS

INPUT POWER	230V, 50 Hz
POWER CONSUMPTION	30W
INLET PRESSURE	2 - 6 bar
OPERATING FLOW RATE	16 - 20 L/min
PRESSURE DROP	0.5bar in service mode
VOLUME CAPACITY	3000L @ 250mg/L CaCO ₃ incoming water hardness
SALT CONSUMPTION	2.5 - 4.0 kg per regeneration
REGENERATION	80 - 110 minutes
REGENERATION WATER	250 L
MEDIA	25L Ecomix® C
INLET / OUTLET	1"
DRY WEIGHT	30kg
DIMENSIONS MM	360W x 565D x 1095H